

# HUBER+SUHNER® DATA SHEET

## Coaxial Cable Connector: 21\_N-50-7-8/133\_N

Rev.: B



### Description

Straight cable jack

Interface Standards

IEC 61169-16\_MIL-STD-348A/304\_CECC 22210



### Technical Data

#### Electrical Data

Impedance 50  $\Omega$   
Interface frequency max. 11 GHz

#### Mechanical Data

Centre contact soldered  
Outer contact clamped  
Weight 0.0495 kg

#### Environmental Data

Operating Temperature -65 °C to 165 °C  
2002/95/EC (RoHS) compliant

#### Material Data

##### Piece Parts

Centre contact Copper Beryllium Alloy  
Outer contact Brass  
Body Brass  
Insulator PFA / PTFE  
Gasket MVQ (Silicone Rubber)

##### Surface Plating

Gold Plating (Nickel underplated)  
SUCOPLATE (R) Plating  
SUCOPLATE (R) Plating

#### Related Documents

Catalogue drawing DOU-00006321  
Assembly instruction DOC-0000179854

#### Ordering Information

Single package 21\_N-50-7-8/133\_NE

#### Additional Information

Suitable cables RG\_213\_/U, GX\_07272, RG\_214\_/U

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com

**HUBER+SUHNER – Excellence in Connectivity Solutions**