

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 21_SK-50-2-51/199_N

Rev.: C



Description

Straight cable jack

Interface Standards
MIL-STD-348A/323



Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	40 GHz
Frequency range	DC to 40 GHz
Return loss	\geq dB

Mechanical Data

Centre contact	plugged
Outer contact	soldered
Weight	0.0029 kg

Environmental Data

Operating Temperature	-55 °C to 125 °C
2002/95/EC (RoHS)	compliant

Material Data

Piece Parts

Centre contact	Copper Beryllium Alloy
Outer contact	Stainless Steel
Body	Stainless Steel
Insulator	PPO_PPE

Surface Plating

Gold Plating (Nickel underplated)

Related Documents

Outline drawing	DOU-00007437
Assembly instruction	DOC-0000182173

Ordering Information

Single package	21_SK-50-2-51/199_NE
----------------	----------------------

Additional Information

Suitable cable	EZ_118_TP
----------------	-----------

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions