

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 21_SMA-50-3-18/111_Y



Description

Straight cable jack

Interface Standards

IEC 60169-15_MIL-STD-348A/310_CECC 22110



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 18 GHz

Mechanical Data

Centre contact soldered
Outer contact soldered

Environmental Data

Operating Temperature -65 °C to 165 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts

| | |
|----------------|------------------------|
| Centre contact | Copper Beryllium Alloy |
| Outer contact | Brass |
| Body | Brass |
| Insulator | PFA / PTFE |

Surface Plating

SUCOPRO Plating
SUCOPRO Plating
SUCOPRO Plating

Related Documents

| | |
|----------------------|----------------|
| Outline drawing | DOU-00047115 |
| Assembly instruction | DOC-0000179086 |

Ordering Information

| | |
|----------------------|-----------------------|
| Bulk 100 pcs package | 21_SMA-50-3-18/111_YH |
|----------------------|-----------------------|

Additional Information

| | |
|-----------------|--|
| Suitable cables | EZ_141_TP_M17, SUCOFORM_141, MULTIFLEX_141 |
|-----------------|--|

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions