

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 21_SMA-50-3-5/111_N

Rev.: B



Description

Straight cable jack

Interface Standards

IEC 60169-15_MIL-STD-348A/310_CECC 22110



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 18 GHz

Mechanical Data

Centre contact soldered
Outer contact crimped
Weight 0.0029 kg

Environmental Data

Operating Temperature -65 °C to 165 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts

Centre contact
Outer contact
Body
Insulator
Crimp ferrule

Material

Copper Beryllium Alloy
Copper Beryllium Alloy
Copper Beryllium Alloy
PFA / PTFE
Copper

Surface Plating

Gold Plating (Nickel underplated)
Gold Plating (Nickel underplated)
Gold Plating (Nickel underplated)
Gold Plating (without Nickel underplating)

Related Documents

Outline drawing DOU-00006289
Catalogue drawing DOU-00005889
Assembly instruction DOC-0000179078

Ordering Information

Single package 21_SMA-50-3-5/111_NE

Additional Information

Suitable cables RG_58_C/U, G_03232, GX_03272

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

HUBER+SUHNER – Excellence in Connectivity Solutions



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com