

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 24_BNO-0-4-1/133_N

Rev.: C



Description

Straight bulkhead cable feed through

Interface Standards
IEC 60169-22



Technical Data

Electrical Data

Impedance not defined Ω
Interface frequency max. 0.2 GHz

Mechanical Data

Centre contact soldered
Outer contact crimped
Weight 0.0202 kg

Environmental Data

Operating Temperature -50 °C to 125 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts

Centre contact	Copper Beryllium / Brass
Outer contact	Brass
Body	Brass
Insulator	ETFE
Gasket	MVQ (Silicone Rubber)
Fastening nut	Brass
Washer	Bronze
Crimp ferrule	Copper

Surface Plating

Gold Plating (Nickel underplated)
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating

Related Documents

Outline drawing	DOU-00008925
Catalogue drawing	DCA-00008927
Assembly instruction	DOC-0000180938
Mounting hole	DOU-00008751

Ordering Information

Single package 24_BNO-0-4-1/133_NE

Additional Information

Suitable cables RG_108_A/U, K 05790

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

HUBER+SUHNER – Excellence in Connectivity Solutions



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com