

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 24_BNT-50-2-1/103_N

Rev.: D



Description

Straight bulkhead cable feed through

Interface Standards
SUHNER-BNT



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 3 GHz

Mechanical Data

Centre contact soldered
Outer contact clamped
Weight 0.0257 kg

Environmental Data

Operating Temperature -50 °C to 125 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts

Centre contact	Copper Beryllium Alloy
Outer contact	Bronze
Body	Brass
Insulator	PFA / PTFE
Gasket	MVQ (Silicone Rubber)
Fastening nut	Brass
Washer	Bronze

Surface Plating

Gold Plating (Nickel underplated)
Silver Plating
SUCOPLATE (R) Plating

SUCOPLATE (R) Plating
SUCOPLATE (R) Plating

Related Documents

Outline drawing	DOU-00048068
Catalogue drawing	DCA-00009150
Assembly instruction	DOC-0000179264
Mounting hole	DOU-00008751

Ordering Information

Single package 24_BNT-50-2-1/103_NE

Additional Information

Suitable cable G_02332

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions