

# HUBER+SUHNER® DATA SHEET

## Coaxial Cable Connector: 24\_MCX-50-1-13/111\_N



### Description

Straight bulkhead cable feed through

Interface Standards  
IEC 60169-36\_CECC 22220

### Technical Data

#### Electrical Data

Impedance 50  $\Omega$   
Interface frequency max. 6 GHz

#### Mechanical Data

Centre contact crimped  
Outer contact crimped  
Weight 0.0018 kg

#### Environmental Data

Operating Temperature -55 °C to 155 °C  
2002/95/EC (RoHS) compliant

#### Material Data

##### Piece Parts

Centre contact	Copper Beryllium Alloy
Outer contact	Brass
Body	Brass
Insulator	PFA / PTFE
Fastening nut	Brass
Washer	Bronze
Crimp ferrule	Copper

##### Surface Plating

Gold Plating (Nickel underplated)
Gold Plating (Nickel underplated)
Gold Plating (Nickel underplated)
Gold Plating (Nickel underplated)
Gold Plating (Nickel underplated)
Gold Plating (Nickel underplated)
Gold Plating (without Nickel underplating)

#### Related Documents

Outline drawing	DOU-00008913
Catalogue drawing	DCA-00008915
Assembly instruction	DOC-0000182201
Mounting hole	DOU-00008855

#### Ordering Information

Bulk 100 pcs package 24\_MCX-50-1-13/111\_NH

#### Additional Information

Suitable cables RG\_178\_B/U, ENVIROFLEX\_178, RG\_196\_A/U



HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

**HUBER+SUHNER – Excellence in Connectivity Solutions**



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com