

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 24_N-50-3-51/19-_N



Description

Straight bulkhead cable feed through

Interface Standards

IEC 61169-16_MIL-STD-348A/304_CECC 22210



Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	18 GHz
Frequency range	DC GHz
Return loss	\geq dB

Mechanical Data

Centre contact	plugged
Outer contact	soldered
Weight	0.0484 kg

Environmental Data

Operating Temperature	-55 °C to 70 °C
2002/95/EC (RoHS)	compliant

Material Data

Piece Parts

Centre contact	Copper Beryllium Alloy
Outer contact	Stainless Steel
Body	Stainless Steel / Brass
Insulator	Air Dielectric - Bead - PPH
Gasket	NR (Natural Rubber)
Fastening nut	Brass
Washer	Brass

Surface Plating

Gold Plating (Nickel underplated)

SUCOPLATE (R) Plating
SUCOPLATE (R) Plating

Related Documents

Catalogue drawing	DCA-00009706
Assembly instruction	DOC-0000180866

Ordering Information

Single package	24_N-50-3-51/19-_NE
----------------	---------------------

Additional Information

Suitable cable	EZ_141_TP_M17
----------------	---------------

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions