

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 24_QLA-01-2-11/112_N

Rev.: B



Description

Straight bulkhead cable feed through

Interface Standards

NIM-CAMAC-Standard CD/N549



Technical Data

Electrical Data

Impedance other Ω
Interface frequency max. 1.4 GHz

Mechanical Data

Centre contact soldered
Outer contact clamped
Weight 0.0051 kg

Environmental Data

Operating Temperature -55 °C to 150 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts

Centre contact	Copper Beryllium Alloy
Outer contact	Bronze
Body	Brass
Insulator	PFA / PTFE
Fastening nut	Brass
Washer	Brass

Surface Plating

Gold Plating (Nickel underplated)
Gold Plating (Nickel underplated)
Nickel Plating
Nickel Plating
Nickel Plating
Nickel Plating

Related Documents

Catalogue drawing	DCA-00009270
Assembly instruction	DOC-0000180116
Mounting hole	DOU-00009113

Ordering Information

Single package 24_QLA-01-2-11/112_NE

Additional Information

Suitable cables RG_316_/U, RG_188_A/U, RG_174_/U

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

HUBER+SUHNER – Excellence in Connectivity Solutions



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com