

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 24_QN-50-3-1/133_N



Description

Straight bulkhead cable feed through

Interface Standards
QN QLF compliant



Technical Data

Electrical Data

Impedance	50 Ω		
Interface frequency max.	11 GHz		
Frequency range	DC to 2 GHz	2 to 3 GHz	3 to 6 GHz
Return loss	≥ 32 dB	≥ 30 dB	≥ 18 dB

Mechanical Data

Centre contact	crimped
Outer contact	crimped
Weight	0.02 kg

Environmental Data

Operating Temperature	-40 °C to 125 °C
2002/95/EC (RoHS)	compliant

Material Data

Piece Parts

Centre contact	Bronze
Outer contact	Brass
Body	Brass
Insulator	PFA / PTFE
Gasket	MVQ
Fastening nut	Brass
Washer	Bronze
Crimp ferrule	Copper

Surface Plating

SUCOPRO Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating

Related Documents

Outline drawing	DOU-00008980
Catalogue drawing	DCA-00008982
Assembly instruction	DOC-0000185136
Mounting hole	DOU-00008737

Ordering Information

Single package	24_QN-50-3-1/133_NE
----------------	---------------------

Additional Information

Suitable cables	ENVIROFLEX_142, RG_223_/U, RG_142_B/U
-----------------	---------------------------------------

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions