

# HUBER+SUHNER® DATA SHEET

## Coaxial Cable Connector: 24\_TNC-50-2-31/133\_N



### Description

Straight bulkhead cable feed through

Interface Standards

IEC 60169-17\_MIL-STD-348A/313\_CECC 22200



### Technical Data

#### Electrical Data

Impedance	50 $\Omega$
Interface frequency max.	11 GHz
Frequency range	DC to 2.5 GHz
Return loss	$\geq 35$ dB

#### Mechanical Data

Centre contact	soldered
Outer contact	soldered
Weight	0.0183 kg

#### Environmental Data

Operating Temperature	-65 °C to 165 °C
2002/95/EC (RoHS)	compliant

#### Material Data

##### Piece Parts

Centre contact	Copper Beryllium Alloy
Outer contact	Brass
Body	Brass
Insulator	PFA / PTFE
Gasket	MVQ (Silicone Rubber)
Fastening nut	Brass
Washer	Bronze

##### Surface Plating

Gold Plating (Nickel underplated)  
SUCOPLATE (R) Plating  
SUCOPLATE (R) Plating

SUCOPLATE (R) Plating  
SUCOPLATE (R) Plating

### Related Documents

Outline drawing	DOU-00008845
Catalogue drawing	DCA-00008847
Assembly instruction	DOC-0000185023
Mounting hole	DOU-00008751

### Ordering Information

Single package	24_TNC-50-2-31/133_NE
----------------	-----------------------

### Additional Information

Suitable cable	EZ_86_TP_M17
----------------	--------------

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com

**HUBER+SUHNER – Excellence in Connectivity Solutions**