

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 25_716-50-7-2/003_-



Description

Straight panel cable jack, flange mount

Interface Standards

IEC 61169-4_CECC 22190_DIN 47223_VG 95250

Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 7.5 GHz

Mechanical Data

Centre contact crimped
Outer contact crimped
Weight 0.1113 kg

Environmental Data

Operating Temperature -65 °C to 165 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts

Centre contact	Bronze / Brass
Outer contact	Bronze
Body	Brass
Insulator	PFA / PTFE
Gasket	NR (Natural Rubber)
Crimp ferrule	Brass

Surface Plating

Silver Plating
Silver Plating
SUCOPLATE (R) Plating

SUCOPLATE (R) Plating

Related Documents

Outline drawing	DOU-00008825
Catalogue drawing	DCA-00008827
Assembly instruction	DOC-0000179881
Mounting hole	DOU-00008824

Ordering Information

Single package	25_716-50-7-2/003_-E
Bulk 100 pcs package	25_716-50-7-2/003_-H

Additional Information

Suitable cables RG_214_U, GX_07272_D

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions