

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 25_N-50-3-7/133_N




Description

Straight panel cable jack, flange mount

Interface Standards

IEC 61169-16_MIL-STD-348A/304_CECC 22210



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 11 GHz

Mechanical Data

Centre contact crimped
Outer contact crimped
Weight 0.0381 kg

Environmental Data

Operating Temperature -65 °C to 165 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts

| | |
|----------------|------------------------|
| Centre contact | Copper Beryllium Alloy |
| Outer contact | Brass |
| Body | Brass |
| Insulator | PFA / PTFE |
| Crimp ferrule | Copper |

Surface Plating

Gold Plating (Nickel underplated)
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating

Related Documents

| | |
|----------------------|----------------|
| Outline drawing | DOU-00009373 |
| Catalogue drawing | DCA-00009038 |
| Assembly instruction | DOC-0000179851 |
| Mounting hole | DOU-00008795 |

Ordering Information

| | |
|----------------------|--------------------|
| Single package | 25_N-50-3-7/133_NE |
| Bulk 100 pcs package | 25_N-50-3-7/133_NH |

Additional Information

| | |
|-----------------|---------------------------|
| Suitable cables | RG_223_/U, ENVIROFLEX_142 |
|-----------------|---------------------------|

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions