# HUBER+SUHNER® DATA SHEET Coaxial Panel Connector: 12 TNC-50-0-1/133 N



### Description

Straight bulkhead receptacle plug

Interface standards IEC 60169-17 MIL-STD-348A/313 CECC 22200



#### **Technical Data** Electrical Det

Electrical Data	
Impedance	<b>50</b> Ω
Interface frequency max.	11 GHz
Mechanical Data	
Weight	0.0211 kg

### **Environmental Data**

**Operating Temperature** 2002/95/EC (RoHS)

### -65 °C to 165 °C compliant

Material

Brass

Brass

Brass

Brass

Brass

Bronze

PFA / PTFE

## **Material Data**

**Piece Parts** Centre contact Outer contact Body Insulator Coupling nut Gasket Fastening nut Washer

### **Related Documents**

Outline drawing Catalogue drawing Mounting hole

### **Ordering Information**

Bulk 100 pcs package	
Single package	

DOU-00010222 DCA-00010224 DOU-00008762

MVQ (Silicone Rubber)

12 TNC-50-0-1/133 NH 12\_TNC-50-0-1/133\_NE

### **Surface Plating**

Gold Plating (Nickel underplated) SUCOPLATE (R) Plating SUCOPLATE (R) Plating

SUCOPLATE (R) Plating

SUCOPLATE (R) Plating SUCOPLATE (R) Plating

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVERI

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

HUBER+SUHNER – Excellence in Connectivity Solutions

Fax

**HUBER+SUHNER** 

HUBER+SUHNER AG **RF** Technology

www.hubersuhner.com

9100 Herisau, Switzerland

Phone +41 (0)71 353 41 11 +41 (0)71 353 45 90