


# SMA 50 Ohm Straight Crimp Type Bulkhead Jack (3-piece) - Solder or Crimp Captivated Contact



| CABLE TYPE        | VSWR & FREQ. RANGE            | GOLD PLATED  | NICKEL PLATED | "A"         |
|-------------------|-------------------------------|--------------|---------------|-------------|
| RG-58/U, 141, 303 | 1.15 + .01 f (GHz) 0-12.4 GHz | 142-0307-411 | 142-0307-416  | .385 (9.78) |


1. Identify connector parts. (3 piece parts - except bulkhead)
2. Strip cable to dimensions shown. Do not nick braid or center conductor. Tin center conductor if contact will be solder attached. Do not tin center conductor if contact is to be crimp attached. When stripping LMR-100 low loss cable, remove foil back to where cable jacket is stripped. A wire stripper of correct size is recommended for this step. Slide heat shrink (as applicable) and crimp sleeve onto jacket of cable.
3. Assemble contact onto cable as shown.

**Solder Attachment:** Solder contact to center conductor through solder hole using .020 (0.51) diameter solder. Use a minimum amount of solder for a good joint.






**Crimp Attachment:** Crimp contact to center conductor using Johnson Components™ Hand Tool 144-0000-910, setting #2, with positioner 141-0000-907. Crimp location should be centered between end of contact and X-hole. Crimp attachment to solid center conductor cables is not recommended.

4. Flare braid and slide body assembly over contact and under braid. Then seat body assembly firmly onto contact. The cable may have to be held in a clamping fixture. Arrange braid uniformly around crimp stem. Slide crimp sleeve forward and crimp using recommended crimp tool. Slide heat shrink forward and shrink (as applicable).

Mounting hole layout



| CABLE GROUP          | PART NUMBER      | CRIMP HEX   |
|----------------------|------------------|-------------|
| RG-58/u,<br>141, 303 | 142-0307-411/416 | .213 (5.41) |



# SMA - 50 Ohm Connectors

## Specifications

## ELECTRICAL RATINGS

**Impedance:** 50 ohms

**Frequency Range:**

|                                                                             |            |
|-----------------------------------------------------------------------------|------------|
| Dummy loads .....                                                           | 0-2 GHz    |
| Flexible cable connectors .....                                             | 0-12.4 GHz |
| Uncabled receptacles, RA semi-rigid and adapters .....                      | 0-18.0 GHz |
| Straight semi-rigid cable connectors and field replaceable connectors ..... | 0-26.5 GHz |

**VSWR:** (f = GHz)

|                                                        | Straight<br>Cabled Connectors | Right Angle<br>Cabled Connectors |
|--------------------------------------------------------|-------------------------------|----------------------------------|
| RG-178 cable .....                                     | 1.20 + .025f                  | 1.20 + .03f                      |
| RG-316, LMR-100 cable .....                            | 1.15 + .02f                   | 1.15 + .03f                      |
| RG-58, LMR-195 cable .....                             | 1.15 + .01f                   | 1.15 + .02f                      |
| RG-142 cable .....                                     | 1.15 + .01f                   | 1.15 + .02f                      |
| LMR-200, LMR-240 cable .....                           | 1.10 + .03f                   | 1.10 + .06f                      |
| .086 semi-rigid .....                                  | 1.07 + .008f                  | 1.18 + .015f                     |
| .141 semi-rigid (w/contact) .....                      | 1.05 + .008f                  | 1.15 + .015f                     |
| .141 semi-rigid (w/o contact) .....                    | 1.035 + .005f                 |                                  |
| Jack-bulkhead jack adapter and plug-plug adapter ..... | 1.05 + .01f                   |                                  |
| Jack-jack adapter and plug-jack adapter .....          | 1.05 + .005f                  |                                  |
| Uncabled receptacles, dummy loads .....                | N/A                           |                                  |
| Field replaceable (see page 59) .....                  | N/A                           |                                  |

**Working Voltage:** (Vrms maximum)\*

| Connectors for Cable Type                                                                     | Sea Level | 70K Feet |
|-----------------------------------------------------------------------------------------------|-----------|----------|
| RG-178 .....                                                                                  | 170       | 45       |
| RG-316; LMR-100, 195, 200 .....                                                               | 250       | 65       |
| RG-58, RG-142, LMR-240, .086 semi-rigid, uncabled receptacles, .141 semi-rigid w/o contact... | 335       | 85       |
| .141 semi-rigid with contact and adapters .....                                               | 500       | 125      |
| Dummy loads .....                                                                             | N/A       |          |

**Dielectric Withstanding Voltage:** (VRMS minimum at sea level)\*

|                                                                                                       |      |
|-------------------------------------------------------------------------------------------------------|------|
| Connectors for RG-178 .....                                                                           | 500  |
| Connectors for RG-316; LMR-100, 195, 200 .....                                                        | 750  |
| Connectors for RG-58, RG-142, LMR-240, .086 semi-rigid, field replaceable, uncabled receptacles ..... | 1000 |
| Connectors for .141 semi-rigid with contact and adapters .....                                        | 1500 |
| Connectors for .141 semi-rigid w/o contact, dummy loads .....                                         | N/A  |

**Corona Level:** (Volts minimum at 70,000 feet)\*

|                                                                                                                 |     |
|-----------------------------------------------------------------------------------------------------------------|-----|
| Connectors for RG-178 .....                                                                                     | 125 |
| Connectors for RG-316; LMR-100, 195, 200 .....                                                                  | 190 |
| Connectors for RG-58, RG-142, LMR-240, .086 semi-rigid, uncabled receptacles, .141 semi-rigid w/o contact ..... | 250 |
| Connectors for .141 semi-rigid with contact and adapters .....                                                  | 375 |
| Dummy loads .....                                                                                               | N/A |

**Corona Level:** (Volts minimum at 70,000 feet)\*

|                                                                                                                 |     |
|-----------------------------------------------------------------------------------------------------------------|-----|
| Connectors for RG-178 .....                                                                                     | 125 |
| Connectors for RG-316; LMR-100, 195, 200 .....                                                                  | 190 |
| Connectors for RG-58, RG-142, LMR-240, .086 semi-rigid, uncabled receptacles, .141 semi-rigid w/o contact ..... | 250 |
| Connectors for .141 semi-rigid with contact and adapters .....                                                  | 375 |
| Dummy loads .....                                                                                               | N/A |

**Insertion Loss:** (dB maximum)

|                                                            |      |                                    |
|------------------------------------------------------------|------|------------------------------------|
| Straight flexible cable connectors and adapters .....      | 0.06 | $\sqrt{f}$ (GHz), tested at 6 GHz  |
| Right angle flexible cable connectors .....                | 0.15 | $\sqrt{f}$ (GHz), tested at 6 GHz  |
| Straight semi-rigid cable connectors with contact .....    | 0.03 | $\sqrt{f}$ (GHz), tested at 10 GHz |
| Right angle semi-rigid cable connectors .....              | 0.05 | $\sqrt{f}$ (GHz), tested at 10 GHz |
| Straight semi-rigid cable connectors w/o contact .....     | 0.03 | $\sqrt{f}$ (GHz), tested at 16 GHz |
| Straight low loss flexible cable connectors .....          | 0.06 | $\sqrt{f}$ (GHz), tested at 1 GHz  |
| Right Angle low loss flexible cable connectors .....       | 0.15 | $\sqrt{f}$ (GHz), tested at 1 GHz  |
| Uncabled receptacles, field replaceable, dummy loads ..... |      | N/A                                |

**Insulation Resistance:** 5000 megohms minimum

**Contact Resistance:** (milliohms maximum) Initial After Environmental

|                                                                            |      |      |
|----------------------------------------------------------------------------|------|------|
| Center contact (straight cabled connectors and uncabled receptacles) ..... | 3.0* | 4.0* |
| Center contact (right angle cabled connectors and adapters) .....          | 4.0  | 6.0  |
| Field replaceable connectors .....                                         | 6.0  | 8.0  |
| Outer contact (all connectors) .....                                       | 2.0  | N/A  |
| Braid to body (gold plated connectors) .....                               | 0.5  | N/A  |
| Braid to body (nickel plated connectors) .....                             | 5.0  | N/A  |

\*N/A where the cable center conductor is used as a contact

**RF Leakage:** (dB minimum, tested at 2.5 GHz)

|                                                                                                                     |        |
|---------------------------------------------------------------------------------------------------------------------|--------|
| Flexible cable connectors, adapters and .141 semi-rigid connectors w/o contact .....                                | -60 dB |
| Field replaceable w/o EMI gasket .....                                                                              | -70 dB |
| .086 semi-rigid connectors and .141 semi-rigid connectors with contact, and field replaceable with EMI Gasket ..... | -90 dB |
| Two-way adapters .....                                                                                              | -90 dB |
| Uncabled receptacles, dummy loads .....                                                                             | N/A    |

**RF High Potential Withstanding Voltage:** (Vrms minimum, tested at 4 and 7 MHz)\*

|                                                                                                                       |      |
|-----------------------------------------------------------------------------------------------------------------------|------|
| Connectors for RG-178 .....                                                                                           | 335  |
| Connectors for RG-316; LMR-100, 195, 200 .....                                                                        | 500  |
| Connectors for RG-58, RG-142, LMR-240, .086 semi-rigid, .141 semi-rigid cable w/o contact, uncabled receptacles ..... | 670  |
| Connectors for .141 semi-rigid with contact and adapters .....                                                        | 1000 |

**Power Rating (Dummy Load):** 0.5 watt @ + 25°C, derated to 0.25 watt @ +125°C

## MECHANICAL RATINGS

**Engagement Design:** MIL-C-39012, Series SMA

**Engagement/Disengagement Force:** 2 inch-pounds maximum

**Mating Torque:** 7 to 10 inch-pounds

**Bulkhead Mounting Nut Torque:** 15 inch-pounds

**Coupling Proof Torque:** 15 inch-pounds minimum

**Coupling Nut Retention:** 60 pounds minimum

**Contact Retention:**

6 lbs. minimum axial force (captivated contacts)

4 inch-ounce minimum torque (uncabled receptacles)

**Cable Retention:**

|                                      | Axial Force*(lbs) | Torque (in-oz) |
|--------------------------------------|-------------------|----------------|
| Connectors for RG-178 .....          | 10                | N/A            |
| Connectors for RG-316, LMR-100 ..... | 20                | N/A            |
| Connectors for LMR-195, 200 .....    | 30                | N/A            |
| Connectors for RG-58, LMR-240 .....  | 40                | N/A            |
| Connectors for RG-142 .....          | 45                | N/A            |
| Connectors for .086 semi-rigid ..... | 30                | 16             |
| Connectors for .141 semi-rigid ..... | 60                | 55             |

\*Or cable breaking strength whichever is less.

**Durability:** 500 cycles minimum

100 cycles minimum for .141 semi-rigid connectors w/o contact

(Meets or exceed the applicable paragraph of MIL-C-39012)

**Shock:** MIL-STD-202, Method 213, Condition I

**Vibration:** MIL-STD-202, Method 204, Condition D

**Moisture Resistance:** MIL-STD-202, Method 106

## ENVIRONMENTAL RATINGS

**Temperature Range:** - 65°C to + 165°C

**Thermal Shock:** MIL-STD-202, Method 107, Condition B

**Corrosion:** MIL-STD-202, Method 101, Condition B

†Avoid user injury due to misapplication. See safety advisory definitions inside front cover.

# SMA - 50 Ohm Connectors

## Specifications

## MATERIAL SPECIFICATIONS

**Bodies:** Brass per QQ-B-626, gold plated\* per MIL-G-45204 .00001" min. or nickel plated per QQ-N-290

**Contacts:** Male - brass per QQ-B-626, gold plated per MIL-G-45204 .00003" min.

Female - beryllium copper per QQ-C-530, gold plated per MIL-G-45204 .00003" min.

**Nut Retention Spring:** Beryllium copper per QQ-C-533. Unplated

**Insulators:** PTFE fluorocarbon per ASTM D 1710 and ASTM D 1457 or Tefzel per ASTM D 3159 or PFA 340 per ASTM

**Expansion Caps:** Brass per QQ-B-613, gold plated per MIL-G-45204 .00001" min. or nickel plated per QQ-N-290

**Crimp Sleeves:** Copper per WW-T-799 or brass per QQ-B-613, gold plated per MIL-G-45204 .00001" min. or nickel plated per QQ-N-290



**Mounting Hardware:** Brass per QQ-B-626 or QQ-B-613, gold plated per MIL-G-45204 .00001" min. or nickel plated per QQ-N-290

**Seal Rings:** Silicone rubber per ZZ-R-765

**EMI Gaskets:** Conductive silicone rubber per MIL-G-83528, Type M

\* All gold plated parts include a .00005" min. nickel underplate barrier layer.

### Mating Engagement for SMA Series per MIL-C-39012



#### NOTES

1. ID OF CONTACT TO MEET VSWR, CONTACT RESISTANCE AND INSERTION WITHDRAWAL FORCES WHEN MATED WITH DIA .0355-.0370 MALE PIN.