

HUBER+SUHNER® DATA SHEET

Coaxial Panel Connector: 22_BNC-50-0-24/100_N

Rev.: E



Description

Straight bulkhead receptacle jack

Interface standards

IEC 60169-8_MIL-STD-348A/301_CECC 22120



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 4 GHz

Mechanical Data

Weight 0.0131 kg

Environmental Data

Operating Temperature -65 °C to 165 °C
2002/95/EC (RoHS) not compliant

Material Data

Piece Parts

Centre contact

Outer contact

Body

Insulator

Gasket

Fastening nut

Washer

Material

Copper Beryllium Alloy

Brass

Brass

PFA / PTFE

MVQ (Silicone Rubber)

Brass

Bronze

Surface Plating

Gold Plating (Nickel underplated)

Silver Plating

Silver Plating

Silver Plating

Silver Plating

Related Documents

Outline drawing DOU-00011233

Catalogue drawing DCA-00011235

Mounting hole DOU-00008762

Ordering Information

Single package 22_BNC-50-0-24/100_NE

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER

HUBER+SUHNER AG

RF Technology

9100 Herisau, Switzerland

Phone +41 (0)71 353 41 11

Fax +41 (0)71 353 45 90

www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions