

# HUBER+SUHNER® DATA SHEET

## Coaxial Panel Connector: 22\_BNC-50-0-3/133\_N



### Description

Straight bulkhead receptacle jack

Interface standards

IEC 60169-8\_MIL-STD-348A/301\_CECC 22120



### Technical Data

#### Electrical Data

Impedance 50  $\Omega$   
Interface frequency max. 4 GHz

#### Mechanical Data

Weight 0.0111 kg

#### Environmental Data

Operating Temperature -65 °C to 165 °C  
2002/95/EC (RoHS) compliant

#### Material Data

##### Piece Parts

Centre contact

Outer contact

Body

Insulator

Gasket

Fastening nut

Washer

##### Material

Copper Beryllium Alloy

Brass

Brass

PFA / PTFE

MVQ (Silicone Rubber)

Brass

Bronze

##### Surface Plating

Gold Plating (Nickel underplated)

SUCOPLATE (R) Plating

SUCOPLATE (R) Plating

SUCOPLATE (R) Plating

SUCOPLATE (R) Plating

### Related Documents

Outline drawing DOU-00010695  
Catalogue drawing DCA-00010697  
Mounting hole DOU-00010411

### Ordering Information

Single package 22\_BNC-50-0-3/133\_NE  
Bulk 100 pcs package 22\_BNC-50-0-3/133\_NH

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**

**RF Technology**

**9100 Herisau, Switzerland**

Phone +41 (0)71 353 41 11

Fax +41 (0)71 353 45 90

www.hubersuhner.com

**HUBER+SUHNER – Excellence in Connectivity Solutions**