HUBER+SUHNER® DATA SHEETCoaxial Panel Connector: 22 BNC-50-0-5/133 N



Description

Straight bulkhead receptacle jack

Interface standards IEC 60169-8 MIL-STD-348A/301 CECC 22120



Technical Data

Electrical Data

 $\begin{array}{ll} \text{Impedance} & \quad \text{50 } \Omega \\ \text{Interface frequency max.} & \quad \text{4 GHz} \end{array}$

Mechanical Data

Weight 0.0074 kg

Environmental Data

Operating Temperature -65 °C to 165 °C 2002/95/EC (RoHS) compliant

Material Data

Piece Parts Material

Centre contact Copper Beryllium Alloy

Outer contact Brass
Body Brass
Insulator PFA / PTFE
Fastening nut Brass
Washer Bronze

Related Documents

Outline drawing DOU-00010863
Catalogue drawing DCA-00010865
Mounting hole DOU-00008762

Ordering Information

 Bulk 100 pcs package
 22_BNC-50-0-5/133_NH

 Single package
 22_BNC-50-0-5/133_NE

Surface Plating

Gold Plating (Nickel underplated) SUCOPLATE (R) Plating SUCOPLATE (R) Plating

SUCOPLATE (R) Plating SUCOPLATE (R) Plating

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

HUBER+SUHNER – Excellence in Connectivity Solutions

HUBER+SUHNER
HUBER+SUHNER AG

RF Technology 9100 Herisau, Switzerland Phone +41 (0)71 353 41 11 Fax +41 (0)71 353 45 90 www.hubersuhner.com

Document: DOC-0000188369 H Issued: 25.10.07 Uncontrolled Copy Page 1/1