

# HUBER+SUHNER® DATA SHEET

## Coaxial Panel Connector: 22\_BNC-75-0-1/133\_N

Rev.: C



### Description

Straight bulkhead receptacle jack

Interface standards

Interface compatible with IEC 61169-8



### Technical Data

#### Electrical Data

Impedance 75  $\Omega$   
Interface frequency max. 1 GHz

#### Mechanical Data

Weight 0.0108 kg

#### Environmental Data

Operating Temperature -65 °C to 165 °C  
2002/95/EC (RoHS) compliant

#### Material Data

##### Piece Parts

Centre contact

Outer contact

Body

Insulator

Gasket

Fastening nut

Washer

##### Material

Copper Beryllium Alloy

Brass

Brass

PFA / PTFE

MVQ (Silicone Rubber)

Brass

Bronze

##### Surface Plating

Gold Plating (Nickel underplated)

SUCOPLATE (R) Plating

SUCOPLATE (R) Plating

SUCOPLATE (R) Plating

SUCOPLATE (R) Plating

### Related Documents

Outline drawing DOU-00010476  
Catalogue drawing DCA-00010478  
Mounting hole DOU-00010411

### Ordering Information

Single package 22\_BNC-75-0-1/133\_NE

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com

**HUBER+SUHNER – Excellence in Connectivity Solutions**