

HUBER+SUHNER® DATA SHEET

Coaxial Panel Connector: 22_N-50-0-3/133_N



Description

Straight bulkhead receptacle jack

Interface standards

IEC 61169-16_MIL-STD-348A/304_CECC 22210



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 11 GHz

Mechanical Data

Weight 0.0465 kg

Environmental Data

Operating Temperature -50 °C to 160 °C
2002/95/EC (RoHS) not compliant

Material Data

Piece Parts

Centre contact
Outer contact
Body
Insulator
Gasket
Fastening nut
Washer

Material

Copper Beryllium / Brass
Brass
Brass
Glas Bead / Air
NR (Natural Rubber)
Brass
Bronze

Surface Plating

Gold Plating (Nickel underplated)
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating

SUCOPLATE (R) Plating
SUCOPLATE (R) Plating

Related Documents

Outline drawing DOU-00011059
Catalogue drawing DCA-00011061

Ordering Information

Single package 22_N-50-0-3/133_NE

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

HUBER+SUHNER – Excellence in Connectivity Solutions



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com