

HUBER+SUHNER® DATA SHEET

Coaxial Panel Connector: 22_QLA-01-0-1/112_N

Rev.: B



Description

Straight bulkhead receptacle jack

Interface standards

NIM-CAMAC-Standard CD/N549



Technical Data

Electrical Data

Impedance other Ω
Interface frequency max. 1.4 GHz

Mechanical Data

Weight 0.0028 kg

Environmental Data

Operating Temperature -55 °C to 150 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts

Centre contact

Outer contact

Body

Insulator

Fastening nut

Washer

Material

Copper Beryllium Alloy

Bronze

Brass

PFA / PTFE

Brass

Bronze

Surface Plating

Gold Plating (Nickel underplated)

Gold Plating (Nickel underplated)

Nickel Plating

Nickel Plating

Nickel Plating

Related Documents

Catalogue drawing

DCA-00010163

Mounting hole

DOU-00009337

Ordering Information

Single package

22_QLA-01-0-1/112_NE

Bulk 100 pcs package

22_QLA-01-0-1/112_NH

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER

HUBER+SUHNER AG

RF Technology

9100 Herisau, Switzerland

Phone +41 (0)71 353 41 11

Fax +41 (0)71 353 45 90

www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions