

# HUBER+SUHNER® DATA SHEET

## Coaxial Panel Connector: 22\_QLA-01-0-2/112\_N

Rev.: A



### Description

Straight bulkhead receptacle jack

Interface standards

NIM-CAMAC-Standard CD/N549



### Technical Data

#### Electrical Data

Impedance other  $\Omega$

Interface frequency max. 1.4 GHz

#### Mechanical Data

Weight 0.0031 kg

#### Environmental Data

Operating Temperature -55 °C to 150 °C

2002/95/EC (RoHS) compliant

#### Material Data

##### Piece Parts

Centre contact

Outer contact

Body

Insulator

Fastening nut

Washer

##### Material

Copper Beryllium Alloy

Bronze

Brass

PFA / PTFE

Brass

Brass

##### Surface Plating

Gold Plating (Nickel underplated)

Gold Plating (Nickel underplated)

Nickel Plating

Nickel Plating

Nickel Plating

### Related Documents

Catalogue drawing

DCA-00010451

Mounting hole

DOU-00009113

### Ordering Information

Single package

22\_QLA-01-0-2/112\_NE

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**

**RF Technology**

**9100 Herisau, Switzerland**

Phone +41 (0)71 353 41 11

Fax +41 (0)71 353 45 90

www.hubersuhner.com

**HUBER+SUHNER – Excellence in Connectivity Solutions**