Data Sheet



Coaxial Panel Connector 22_QMA-50-0-34/133_N

Description

Straight bulkhead receptacle jack

Interface standards

QMA QLF compliant



Technical Data

Electrical Data

 $\begin{array}{ll} \text{Impedance} & 50 \ \Omega \\ \text{Interface frequency max.} & 18 \ \text{GHz} \end{array}$

Environmental Data

Operating temperature $$-40\ ^{\circ}\text{C}$$ to 85 $^{\circ}\text{C}$$ 2011/65/EU (RoHS) compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	

Related Documents

Outline drawing DOU-00111270 Catalogue drawing DCA-00200089

Ordering Information

Bulk 100 pcs package 22_QMA-50-0-34/133_NH

Remarks

With panel seal

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.