

HUBER+SUHNER® DATA SHEET

Coaxial Panel Connector: 22_QN-50-0-1/133_N

Rev.: C



Description

Straight bulkhead receptacle jack

Interface standards
QN QLF compliant



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 11 GHz

Mechanical Data

Weight 0.012 kg

Environmental Data

Operating Temperature -40 °C to 125 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts

Centre contact
Outer contact
Body
Insulator

Material

Bronze
Brass
Brass
PFA / PTFE

Surface Plating

SUCOPRO Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating

Related Documents

Outline drawing DOU-00010244
Catalogue drawing DCA-00010246

Ordering Information

Single package 22_QN-50-0-1/133_NE
Tray package 22_QN-50-0-1/133_NY

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

HUBER+SUHNER – Excellence in Connectivity Solutions



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com