

HUBER+SUHNER® DATA SHEET

Coaxial Panel Connector: 22_SMB-50-0-3/111_N



Description

Straight bulkhead receptacle jack

Interface standards

IEC 60169-10_MIL-STD-348A/311_CECC 22130



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 4 GHz

Mechanical Data

Weight 0.0011 kg

Environmental Data

Operating Temperature -65 °C to 165 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts

Centre contact	Brass
Outer contact	Brass
Body	Brass
Insulator	PFA / PTFE
Fastening nut	Brass
Washer	Bronze

Surface Plating

Hard Au min. 1.3 μm over Ni min. 1.3 μm
Gold Plating (Nickel underplated)
Hard Au min. 0.8 μm over Ni min. 1.3 μm

Hard Au min. 0.8 μm over Ni min. 1.3 μm
Hard Au min. 0.8 μm over Ni min. 1.3 μm

Related Documents

Outline drawing	DOU-00010420
Catalogue drawing	DCA-00010422
Mounting hole	DOU-00008855

Ordering Information

Bulk 100 pcs package	22_SMB-50-0-3/111_NH
Single package	22_SMB-50-0-3/111_NE

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

HUBER+SUHNER – Excellence in Connectivity Solutions



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com