

HUBER+SUHNER® DATA SHEET

Coaxial Panel Connector: 23_716-50-0-57/003_-

Rev.: C



Description

Straight panel receptacle jack, flange mount

Interface standards

IEC 61169-4_CECC 22190_DIN 47223_VG 95250



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 7.5 GHz

Mechanical Data

Weight 0.0798 kg

Environmental Data

Operating Temperature -65 °C to 165 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts

Centre contact
Outer contact
Body
Insulator

Material

Bronze
Brass
Brass
PFA / PTFE

Surface Plating

Silver Plating
Silver Plating
SUCOPLATE (R) Plating

Related Documents

Outline drawing DOU-00010926
Catalogue drawing DCA-00010928

Ordering Information

Bulk 20 pcs package 23_716-50-0-57/003_-V

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions