

# HUBER+SUHNER® DATA SHEET

## Coaxial Panel Connector: 23\_PC35-50-0-53/199\_U



### Description

Straight panel receptacle jack, flange mount

Interface standards  
IEC 60169-23



### Technical Data

#### Electrical Data

Impedance 50  $\Omega$   
Interface frequency max. 33 GHz

#### Mechanical Data

Weight 0.0035 kg

#### Environmental Data

Operating Temperature -65 °C to 90 °C  
2002/95/EC (RoHS) compliant

#### Material Data

##### Piece Parts

Centre contact  
Outer contact  
Body  
Insulator

##### Material

Copper Beryllium Alloy  
Stainless Steel  
Stainless Steel  
PS

##### Surface Plating

Gold Plating (without Nickel underplating)

### Related Documents

Outline drawing DOU-00011352  
Catalogue drawing DCA-00011353

### Ordering Information

Single package 23\_PC35-50-0-53/199\_UE

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

**HUBER+SUHNER – Excellence in Connectivity Solutions**



**HUBER+SUHNER AG**  
**RF Technology**  
**9100 Herisau, Switzerland**  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
[www.hubersuhner.com](http://www.hubersuhner.com)