HUBER+SUHNER® DATA SHEET Coaxial Panel Connector: 23_SMA-50-0-1/111_N



Description

Straight panel receptacle jack, flange mount

Interface standards IEC 60169-15 MIL-STD-348A/310 CECC 22110



 $\begin{array}{ll} \text{Impedance} & \quad 50~\Omega \\ \text{Interface frequency max.} & \quad 18~\text{GHz} \end{array}$

Mechanical Data

Weight 0.0025 kg

Environmental Data

Operating Temperature -65 °C to 165 °C 2002/95/EC (RoHS) compliant

Material Data

Piece Parts Material

Centre contact Copper Beryllium Alloy
Outer contact Copper Beryllium Alloy
Body Copper Beryllium Alloy
Insulator PFA / PTFE

Related Documents

Catalogue drawing DCA-00010331

Ordering Information

 Bulk 100 pcs package
 23_SMA-50-0-1/111_NH

 Single package
 23_SMA-50-0-1/111_NE

Surface Plating

Gold Plating (Nickel underplated) Gold Plating (Nickel underplated) Gold Plating (Nickel underplated)

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

Document: DOC-0000187989 J

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

HUBER+SUHNER – Excellence in Connectivity Solutions

HUBER+SUHNER
HUBER+SUHNER AG

RF Technology 9100 Herisau, Switzerland Phone +41 (0)71 353 41 11 Fax +41 (0)71 353 45 90 www.hubersuhner.com

Issued: 26.10.07 Uncontrolled Copy