

HUBER+SUHNER® DATA SHEET

EMP Protector: 3403.17.0042




Description

Fine protector hybrid technology

Benefits

Broad-band operation
DC continuity for outdoor powering
With GDT 9071.99.0548, 90 V
Compliant to IEC 61643-21



Product Configuration

Main path connectors Port 1: unprotected, N jack (female) - Port 2: protected, N jack (female)
Mounting and grounding M4 (M=screw)

Technical Data

Electrical Data

Impedance	50 Ω
Frequency range	650 to 2500 MHz
Return loss	≥ 20.8 dB
Insertion loss	≤ 0.5 dB
RF CW power	≤ 50 W
PIM 3 rd order	not specified
DC voltage	≤ 15 V
DC current	≤ 3 A
Surge current handling capability	30 single / 20 multiple kA (test pulse 8/20 μ s)
Residual pulse energy	6 μ J typically (test pulse 4 kV 1.2/50 μ s / 2 kA 8/20 μ s) main path - protected side

Mechanical Data

Weight 330 g

Environmental Data

Operating temperature -40 °C to +85 °C
Waterproof degree IP 65 (according to IEC 60529, data refer to the coupled state)
2002/95/EC (RoHS) Telecom compliant

Material Data

Piece Parts	Material	Surface Plating
Housing	Aluminium	Chromatized
Port 1 center contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Port 2 center contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)

Related Documents

Outline drawing DOU-00018472.1
Mounting instruction DOC-0000176104

Remarks

Recommendation: if this protector is mated with connectors made of copper-alloy base material and trimetal or nickel plating the connector area must be taped to improve long-term durability.

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Protection
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 47 51
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions