

HUBER+SUHNER® DATA SHEET

Coaxial Cable: GX_03272_D-06



Description

PE cross-linked - 50 Ohm - double screen

Technical Data

Construction

	Material	Detail	Diameter
Centre conductor	Copper, Silver plated	Wire	0.88 mm
Dielectric	PEX (Polyethylene cross-linked)		2.95 mm
Outer conductor	Copper, Silver plated	Braid, 96 %	3.6 mm
Outer conductor	Copper, Silver plated	Braid, 94 %	4.2 mm
Jacket	RADOX	RAL 9005 - bk	5.4 mm +/- 0.1
Print	HUBER+SUHNER GX 03272 D-06 50 Ohm (PA no.)		

Electrical Data

Impedance	50 Ω +/- 2
Max. operating frequency	6 GHz
Capacitance	101 pF/m
Velocity of signal propagation	66 %
Signal delay	5.03 ns/m
Insulation resistance	$\geq 1 \times 10^8$ M Ω m
Min. screening effectiveness	>80 dB (up to 6 GHz)
Max. operating voltage	2.5 kV _{rms} (at sea level)
Test voltage	5 kV _{rms} (50 Hz/1 min)

Mechanical Data

Weight	5.5 kg/100 m
Min. bending radius	static 30 mm
	repeated (for max. 50 bendings) 54 mm

Environmental Data

Temperature range	-40 °C... + 105 °C
Installation temperature	-20 °C... + 60 °C
Flammability	IEC 60332-1
Halogen free	IEC 60754
2002/95/EC (RoHS)	compliant

Ordering Information

Order as	GX_03272_D-06
----------	---------------

Additional Information

Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

Suitable Connectors

Cable group	crimped (U9)
	clamped (U10)
	soldered —

HUBER+SUHNER® DATA SHEET

Coaxial Cable: GX_03272_D-06

Rev.: J



Matrix **Attenuation** [formula: $(a \cdot f^{0.5} + b \cdot f)$] **and Power CW** [formula: $(p \cdot f^{0.5})$]

Coefficients:

a=	0.3952	b=	0.0779	f _{max} =	6	p _{at} 1GHz =	205
	Frequency		Nom. attenuation		Nom. attenuation		Max. CW power
	(GHz)		(dB / m)		(dB / ft)		(watt)
			sea level 25° C ambient temperature		sea level 25° C ambient temperature		sea level 40° C ambient temperature
	0.3		0.24		0.073		374
	0.6		0.35		0.107		265
	0.9		0.45		0.137		216
	1.2		0.53		0.162		187
	1.5		0.60		0.183		167
	1.8		0.67		0.204		153
	2.1		0.74		0.226		141
	2.4		0.80		0.244		132
	2.7		0.86		0.262		125
	3.0		0.92		0.280		118
	3.3		0.97		0.296		113
	3.6		1.03		0.314		108
	3.9		1.08		0.329		104
	4.2		1.14		0.347		100
	4.5		1.19		0.363		97
	4.8		1.24		0.378		94
	5.1		1.29		0.393		91
	5.4		1.34		0.408		88
	5.7		1.39		0.424		86
	6.0		1.44		0.439		84

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Industrial
9100 Herisau, Switzerland
 Phone +41 (0)71 353 41 11
 Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions