

HUBER+SUHNER® DATA SHEET

Coaxial Cable: K_02253_D-02



Description

PTFE - 75 Ohm - double screen

Technical Data

Construction

	Material	Detail	Diameter
Centre conductor	Steel, Copper+Silver plated	Strand-07	0.31 mm
Dielectric	PTFE		1.55 mm
Outer conductor	Copper, Silver plated	Braid, 95 %	2 mm
Outer conductor	Copper, Silver plated	Braid, 93 %	2.5 mm
Jacket	FEP	RAL 8015 - br	3 mm +/- 0.1
Print	HUBER+SUHNER K 02253 D-02 75 Ohm (PA no.)		

Electrical Data

Impedance	75 Ω +/- 3
Max. operating frequency	2 GHz
Capacitance	63 pF/m
Velocity of signal propagation	69 %
Signal delay	4.83 ns/m
Insulation resistance	$\geq 1 \times 10^8$ M Ω m
Min. screening effectiveness	>81 dB (up to 2 GHz)
Max. operating voltage	0.75 kV _{rms} (at sea level)
Test voltage	1.5 kV _{rms} (50 Hz/1 min)

Mechanical Data

Weight	2.3 kg/100 m
Min. bending radius	static 18 mm
	repeated (for max. 50 bendings) 30 mm
	dynamic 45 mm

Environmental Data

Temperature range	-65 °C... + 165 °C
Installation temperature	-20 °C... + 60 °C
Flammability	IEC 60332-3
2002/95/EC (RoHS)	compliant

Ordering Information

Order as	K_02253_D-02
----------	--------------

Additional Information

Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

Suitable Connectors

Cable group	crimped (R8)
	clamped (on request)
	soldered —

HUBER+SUHNER® DATA SHEET

Coaxial Cable: K_02253_D-02



Matrix **Attenuation** [formula: $(a \cdot f^{0.5} + b \cdot f)$] **and Power CW** [formula: $(p \cdot f / f^{0.5})$]

Coefficients:

a=	0.9109	b=	0.0308	f _{max} =	2	p _{at} 1GHz =	120
	Frequency		Nom. attenuation		Nom. attenuation		Max. CW power
	(GHz)		(dB / m)		(dB / ft)		(watt)
			sea level 25° C ambient temperature		sea level 25° C ambient temperature		sea level 40° C ambient temperature
	0.1		0.29		0.088		379
	0.2		0.41		0.125		268
	0.3		0.51		0.155		219
	0.4		0.59		0.180		190
	0.5		0.66		0.201		170
	0.6		0.72		0.219		155
	0.7		0.78		0.238		143
	0.8		0.84		0.256		134
	0.9		0.89		0.271		126
	1.0		0.94		0.286		120
	1.1		0.99		0.302		114
	1.2		1.03		0.314		110
	1.3		1.08		0.329		105
	1.4		1.12		0.341		101
	1.5		1.16		0.354		98
	1.6		1.20		0.366		95
	1.7		1.24		0.378		92
	1.8		1.28		0.390		89
	1.9		1.31		0.399		87
	2.0		1.35		0.411		85

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Industrial
9100 Herisau, Switzerland
 Phone +41 (0)71 353 41 11
 Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions