

HUBER+SUHNER® DATA SHEET

Coaxial Cable: RG_214_/U



Description

PE-50 Ohm - double screen

Technical Data

Construction

	Material	Detail	Diameter
Centre conductor	Copper, Silver plated	Strand-07	2.25 mm
Dielectric	PE		7.28 mm
Outer conductor	Copper, Silver plated	Braid, 93 %	8 mm
Outer conductor	Copper, Silver plated	Braid, 95 %	8.7 mm
Jacket	PVC II (low migration)	RAL 9005 - bk	10.8 mm +/- 0.15
Print	HUBER+SUHNER RG 214 U 50 Ohm (PA no.)		

Electrical Data

Impedance	50 Ω +/- 2
Max. operating frequency	6 GHz
Capacitance	101 pF/m
Velocity of signal propagation	66 %
Signal delay	5.03 ns/m
Insulation resistance	$\geq 1 \times 10^8$ M Ω m
Min. screening effectiveness	>71 dB (up to 1 GHz)
Max. operating voltage	5 kV _{rms} (at sea level)
Test voltage	10 kV _{rms} (50 Hz/1 min)

Mechanical Data

Weight	18.5 kg/100 m
Min. bending radius	static 55 mm
	repeated (for max. 50 bendings) 108 mm

Environmental Data

Temperature range	-25 °C... + 85 °C
Installation temperature	-20 °C... + 60 °C
2002/95/EC (RoHS)	compliant

Ordering Information

Order as RG_214_/U

Additional Information

Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

Suitable Connectors

Cable group	crimped (U32)
	clamped (U33)
	soldered —

HUBER+SUHNER® DATA SHEET

Coaxial Cable: RG_214_/U



Matrix **Attenuation** [formula: $(a \cdot f^{0.5} + b \cdot f)$] **and Power CW** [formula: $(p \cdot f / f^{0.5})$]

Coefficients:

a=	0.202	b=	0.063	f _{max} =	6	p _{at} 1GHz =	325
	Frequency		Nom. attenuation		Nom. attenuation		Max. CW power
	(GHz)		(dB / m)		(dB / ft)		(watt)
			sea level 25° C ambient temperature		sea level 25° C ambient temperature		sea level 40° C ambient temperature
	0.3		0.13		0.040		593
	0.6		0.19		0.058		420
	0.9		0.25		0.076		343
	1.2		0.30		0.091		297
	1.5		0.34		0.104		265
	1.8		0.38		0.116		242
	2.1		0.43		0.131		224
	2.4		0.46		0.140		210
	2.7		0.50		0.152		198
	3.0		0.54		0.165		188
	3.3		0.57		0.174		179
	3.6		0.61		0.186		171
	3.9		0.64		0.195		165
	4.2		0.68		0.207		159
	4.5		0.71		0.216		153
	4.8		0.74		0.226		148
	5.1		0.78		0.238		144
	5.4		0.81		0.247		140
	5.7		0.84		0.256		136
	6.0		0.87		0.265		133

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Industrial
9100 Herisau, Switzerland
 Phone +41 (0)71 353 41 11
 Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions