

HUBER+SUHNER® DATA SHEET

Coaxial Cable: SUCOFORM_86_75



Description

SUCOFORM, the handformable microwave cable

Technical Data

Construction

	Material	Detail	Diameter
Centre conductor	Steel, Copper+Silver plated	Wire	0.29 mm
Dielectric	PTFE		1.65 mm
Outer conductor	Copper, Tin plated	Tin soaked braid, 100 %	2.1 mm
Print	HUBER+SUHNER SUCOFORM 86 75 Ohm (PA no.)		

Electrical Data

Impedance	75 Ω +/- 3
Max. operating frequency	4 GHz
Capacitance	62 pF/m
Velocity of signal propagation	71 %
Signal delay	4.7 ns/m
Insulation resistance	$\geq 1 \times 10^8 \text{ M}\Omega\text{m}$
Min. screening effectiveness	>100 dB (up to 4 GHz)
Max. operating voltage	1.5 kV _{rms} (at sea level)
Test voltage	3 kV _{rms} (50 Hz/1 min)

Mechanical Data

Weight	1.4 kg/100 m
Min. bending radius	static 6 mm
	repeated (for max. 50 bendings) 20 mm

Environmental Data

Temperature range	-65 °C... + 165 °C
Installation temperature	-20 °C... + 60 °C
Flammability	IEC 60332-1, UL 1581 § 1080 (VW-1)
2002/95/EC (RoHS)	compliant

Ordering Information

Order as	SUCOFORM_86_75
----------	----------------

Additional Information

Remarks

(For details refer to the HUBER+SUHNER MICROWAVE CABLES AND ASSEMBLIES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

Suitable Connectors

Cable group	crimped (Y4)
	clamped —
	soldered —

HUBER+SUHNER® DATA SHEET

Coaxial Cable: SUCOFORM_86_75



Matrix **Attenuation** [formula: $(a \cdot f^{0.5} + b \cdot f)$] **and Power CW** [formula: $(p \cdot f^{0.5})$]

Coefficients:

a=	0.671	b=	0.0672	f _{max} =	4	p _{at} 1GHz =	120
	Frequency		Nom. attenuation		Nom. attenuation		Max. CW power
	(GHz)		(dB / m)		(dB / ft)		(watt)
			sea level 25° C ambient temperature		sea level 25° C ambient temperature		sea level 40° C ambient temperature
	0.2		0.31		0.094		268
	0.4		0.45		0.137		190
	0.6		0.56		0.171		155
	0.8		0.65		0.198		134
	1.0		0.74		0.226		120
	1.2		0.82		0.250		110
	1.4		0.89		0.271		101
	1.6		0.96		0.293		95
	1.8		1.02		0.311		89
	2.0		1.08		0.329		85
	2.2		1.14		0.347		81
	2.4		1.20		0.366		77
	2.6		1.26		0.384		74
	2.8		1.31		0.399		72
	3.0		1.36		0.415		69
	3.2		1.42		0.433		67
	3.4		1.47		0.448		65
	3.6		1.52		0.463		63
	3.8		1.56		0.475		62
	4.0		1.61		0.491		60

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Industrial
9100 Herisau, Switzerland
 Phone +41 (0)71 353 41 11
 Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions