

HUBER+SUHNER® DATA SHEET

RF TERMINATION: Type 6500.28.A

Rev.: C



Description

Precision Termination, Low Power

Product Configuration

Connector PC 7
Interface standard IEEE STD 287_ANSI C 16.43

Technical Data

Electrical Data

Nominal impedance 50 Ω
Frequency range DC to 18 GHz
Frequency sub range (GHz) DC to 6 6 to 16 16 to 18
VSWR max. 1.03 1.05 1.06
Power rating 0.5 Watt average power up to 30 °C ambient temperature, linearly derated to 0 Watt at 130 °C ambient temperature.

Mechanical Data

Weight 0.05 kg

Material Data

Piece Part

Centre contact Copper Beryllium Alloy
Outer contact Brass
Body Brass
Insulator Air Dielectric - Bead - PS
Coupling nut Brass

Surface Plating

Gold Plating (without Nickel underplating)
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating

Related Documents

Outline drawing DOU-00020124

Ordering Information

Single packaging 6500.28.A



HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Industrial
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions