

# HUBER+SUHNER® DATA SHEET

## RF TERMINATION: Type 65\_N-75-0-11/133\_N

Rev.: D



### Description

Standard Termination, Low Power

### Product Configuration

Connector N plug (male)  
Interface standard IEC 60169-16\_MIL-STD-348A/304\_CECC 22210

### Technical Data

#### Electrical Data

Nominal impedance 75  $\Omega$   
Frequency range DC to 1.3 GHz  
Frequency sub range (GHz) DC to 1 1 to 1.3  
VSWR max. 1.05 1.08  
Power rating 1 Watt average power up to 30 °C ambient temperature, linearly derated to 0 Watt at 130 °C ambient temperature.  
1500 Watt peak power

#### Mechanical Data

Weight 0.044 kg

#### Material Data

##### Piece Part

Centre contact  
Outer contact  
Body  
Insulator  
Coupling nut

##### Material

Brass  
Brass  
Brass  
PFA / PTFE  
Brass

##### Surface Plating

Gold Plating (Nickel underplated)  
SUCOPLATE (R) Plating  
SUCOPLATE (R) Plating  
SUCOPLATE (R) Plating

### Related Documents

Outline drawing On request

### Ordering Information

Single packaging 65\_N-75-0-11/133\_NE



HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**  
**RF Industrial**  
**9100 Herisau, Switzerland**  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
[www.hubersuhner.com](http://www.hubersuhner.com)

**HUBER+SUHNER – Excellence in Connectivity Solutions**