

# HUBER+SUHNER® DATA SHEET

## RF TERMINATION: Type 65\_TNC-75-0-1/133\_N

Rev.: C



### Description

Standard Termination, Low Power

### Product Configuration

Connector TNC plug (male)  
Interface standard IEC 60169-17\_MIL-STD-348A/313\_CECC 22200

### Technical Data

#### Electrical Data

Nominal impedance 75  $\Omega$   
Frequency range DC to 1 GHz  
VSWR max. 1.1  
Power rating 1 Watt average power up to 30 °C ambient temperature, linearly derated to 0 Watt at 130 °C ambient temperature.  
800 Watt peak power

#### Mechanical Data

Weight 0.019 kg

#### Material Data

Piece Part	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating

### Related Documents

Outline drawing On request

### Ordering Information

Single packaging 65\_TNC-75-0-1/133\_NE



HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**  
**RF Industrial**  
**9100 Herisau, Switzerland**  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
[www.hubersuhner.com](http://www.hubersuhner.com)

**HUBER+SUHNER – Excellence in Connectivity Solutions**