

**G**

G Magnetic Mount Series

Black or chrome 3-1/4" diameter magnetic mount; 1-1/8"-18 thread

Model	Length of Coax	Coax	Connector	Type
(R)(B)G-NC	12'	RG-58A/U	None	N/A
(R)(B)GC-NC	12'	RG-58/U	None	N/A
(R)(B)G	12'	RG-58A/U	PL259*	Crimp
(R)(B)GBN	12'	RG-58/U	BNC	Crimp
(R)(B)GC	12'	RG-58/U	TNC	Crimp
(R)GML195C	12'	Pro-Flex™ Plus 195	TNC	Crimp
(R)GP	12'	RG-58/U	Teflon PL259	Solder
(R)(B)GPL	12'	RG-58/U	Mini-UHF	Crimp
RBGFPL	12'	White Teflon	Mini-UHF	Crimp
(R)GML195NCP	12'	Pro-Flex™ Plus 195	N	Crimp
(R)(B)GNCP	12'	RG-58/U	N	Crimp
(R)GML195MSMA	12'	Pro-Flex™ Plus 195	Male SMA	Crimp
(R)GMSMA	12'	RG-58/U	Male SMA	Crimp
(R)(B)GFFME	12'	RG-58/U	Female FME*	Crimp
RGRF240-NC	12'	Pro-Flex™ Plus 240	None	N/A

* This mount uses a small contact button.

Note: Connectors are shipped loose. Connectors may be attached upon request for an additional charge.

(B) prefix indicates black option

(R) prefix indicates an optional rubber boot