

Thick Surface Mounts - BMATM Series



BMATM

3/8" or 3/4" hole; 1-1/8"-18 thread; thick plate; installs from below; can be used for metal thickness to 3/16"

Model	Length of Coax	Coax	Connector	Type
BMATM-NC	17'	RG-58/U	None	N/A
BMATM-NC	25'	RG-58/U	None	N/A
BMATMML195NC	17'	Pro-Flex™ Plus 195	None	N/A
BMATM	17'	RG-58/U	Silver Plated PL259	Solder
BMATMCP	17'	RG-58/U	Silver Plated PL259	Crimp
BMATMLP	17'	RG-8X	Silver Plated Teflon PL259	Solder
BMATMC	17'	RG-58/U	TNC	Crimp
BMATMFC	17'	White Teflon	TNC	Crimp
BMATMMSMA	17'	RG-58/U	Male SMA	Crimp
BMATMNSO	17'	RG-58/U	N	Solder
BMATMPL	17'	RG-58/U	Mini-UHF	Crimp
BMATMFPL	17'	White Teflon	Mini-UHF	Crimp
BMATMLPL	17'	RG-8X	Mini-UHF	Crimp
BMATMMFME	17'	RG-58/U	Male FME*	Crimp
BMATMFFME	17'	RG-58/U	Female FME*	Crimp
BMATM38	None	None	None	N/A
BMAT3ML195//NCP	12'	PFP195	Loose N	Crimp
BMAT3ML195RPC//3	3'	PFP195	Loose RPTNC plug (male)	N/A

*** Connector is installed on these mounts only. For all other mounts, connectors can be attached for an additional charge.**



K794 Series

3/4" Hole Mount for up to 1/2" Thick Roof Thickness

Model	Length of Coax	Coax	Connector
K794	17'	RG-58/U	None
KE794	30'	RG-58/U	None