



HIGH FREQUENCY, HIGH PERFORMANCE PERMANENT 3/4" NMO MOUNT

This permanent NMO mount provides extended frequency range up 5800 MHz. This allows antennas in frequency ranges above traditional LMR frequencies to be deployed.

FEATURES


- High-performance up to 5800 MHz
- 78 Rockwell Hardness brass material resists corrosion
- Silver soldered ground lug and contact virtually
- Gold plated contact provides superior conductivity
- Low loss 17' 195-type coax
- Available in other coax lengths and connector options
- Extended frequency range

MARKETS

- Land mobile radio
- Vehicular

FREQUENCY RANGE (MHz)	INSERTION LOSS PER FOOT OF CABLE (dB)	INSERTION LOSS PER 17FOOT OF CABLE (dB)
150	-0.0965	-0.6178
450	-0.2171	-1.3274
900	-0.3446	-1.9404
1500	-0.5834	-2.6509
1800	-0.5355	-2.9682
2400	-0.4637	-3.2679
2700	-0.5402	-3.6155
4900	-3.5302	-8.0636
5800	-3.2943	-9.0496

MODEL	DESCRIPTION	MOUNTING HOLE TYPE	COAXIAL CABLE	CONNECTOR
MB016394	High frequency mount for all antennas operating at 700-5800MHz	3/4" hole permanent mount	17ft ATX195	Contact customer service for connector options




global solutions: local support™

Americas: +1.847.839.6907
IAS-AmericasEastSales@lairdtech.com

Europe: +1.32.80.7866.12
IAS-EUSales@lairdtech.com

Asia: +1.65.6.243.8022
IAS-AsiaSales@lairdtech.com

INSERTION LOSS PER FOOT OF ATX195 CABLE (DB)



INSERTION LOSS PER 17FEET OF ATX195 CABLE (DB)

