



BGYD806K antenna (top)
and BWC1022 mount
(inset)

Yagi Antennas, 806-896 MHz, 10 dBd gain

The BGYD806K has been engineered to provide high gain broadband performance between the frequencies of 806-896 MHz. Solid 3/8" aluminum elements complement the fully welded dipole on the boom. The black powder coat BGYD806K comes with an integral low loss 2' RG213 feed line with a standard N-Female connector. High strength mounting clamp is supplied for vertical or horizontal polarization.

Features

- Dipole fully-welded to boom
- Black powder coat over stainless steel antenna assembly
- Mounting clamp included
- Antenna is supplied with a 2' pigtail (RG213) and N female connector



Technical Data

Maximum Power: 200 watts
Nominal Impedance: 50 ohms
VSWR: < 1.5:1 Nominal < 1.7:1 Maximum
Radiator Material: Aluminum
Mounting Method: Includes mounting hardware BWC1022

Antenna Electrical Specifications

Model	Frequency Range	-3 dB Horizontal Beamwidth	-3 dB Vertical Beamwidth	Front to Back Ratio	Nominal Gain
BGYD806K	806-896 MHz	60°	46°	20 dB	10 dBd

Mechanical Specifications

Model	Dimensions* (L x W)	Weight (Mass)	Cross Sectional Area	Lateral Thrust @ 100 mph	Rated Wind Velocity**
BGYD806K	24" x 6.8"	2 lbs	0.24 ft ²	6 lbs	125 mph

Model	Elements	Cable Type	Cable Length	Connector Type
BGYD806K	7	RG213	2 ft	N female

* Dimension does not include antenna cable

**120 mph with 1/2" radial ice