
Yagi Antennas, 806-896 MHz, 14 dBd gain

The BMYD806O has been engineered to meet the requirements of a high gain, broadband, premium quality antenna. This antenna provides 14 dBd gain and operates in the 806-896 MHz range. The BMYD806O is manufactured using high strength 6061-T6 aluminum to withstand heavy ice, high wind and other harsh conditions. All elements are welded to the boom and the dipole design has an integral feed line welded to the boom for extra strength and electrical conductivity. This eliminates misalignment or fastener problems. The entire antenna is anodized for appearance and corrosion resistance. A heavy duty clamp is supplied which easily permits horizontal or vertical polarization.

Features

- Elements and boom are manufactured from aircraft quality 6061-T6 aluminum for optimum strength
- Antenna is anodized for corrosion resistance
- Antenna is supplied with a 2' pigtail (RG213) and N female connector





Antenna Electrical Specifications

Model	Frequency Range	-3 dB Horizonal Beamwidth	-3 dB Vertical Beamwidth	Front to Back Ratio	Nominal Gain
BMYD8060	806-896 MHz	36°	30°	25 dB	14 dBd

Mechanical Specifications

Model	Dimensions* (L x W)	Weight (Mass)	Cross Sectional Area	Lateral Thrust @ 100 mph	Rated Wind Velocity**
BMYD806O	60" x 7.3"	3.5 lbs	0.67 ft ²	16.75 lbs	125 mph

Model	Elements	Cable Type	Cable Length	Connector Type
BMYD806O	18	RG213	2 ft	N female

Technical Data

um Power: watts
al Impedance: hms
5:1 Nominal 7:1 Maximum
or Material: ninum 6061-T6
ing Method: udes mounting hardware BWC1001A

^{*} Dimension does not include antenna cable

^{**80} mph with 1/2" radial ice