

16-24GHz Low Noise, Variable Gain Amplifier


GaAs Monolithic Microwave IC

Description

The CHA2292 is a high gain four-stage monolithic low noise amplifier with variable gain. It is designed for a wide range of applications, from military to commercial communication systems. The backside of the chip is both RF and DC grounded. This helps simplify the assembly process.

The circuit is manufactured with a PM-HEMT process, 0.25 μ m gate length, via holes through the substrate, air bridges and electron beam gate lithography.


It is available in chip form.



Main Features

- Frequency range: 17-24GHz
- 2.8dB Noise Figure.
- 25dB gain
- Gain control range: 15dB
- DC power consumption: 160mA @ 5V
- Chip size: 2.32 X 1.23 X 0.10 mm

Typical on wafer measurements :Gain & NF



Main Characteristics

$T_{amb.} = 25^{\circ}$

	Parameter	Min	Typ	Max	Unit
Fop	Operating frequency range	16		24	GHz
G	Small signal gain	24	26		dB
NF	Noise figure		2.8	3.5	dB
Gctrl	Gain control range with Vc variation	15	20		dB
Id	Bias current		160		mA

ESD Protection : Electrostatic discharge sensitive device. Observe handling precautions !

Electrical Characteristics for Broadband OperationT_{amb} = +25°C, V₅=V_{d2,3,4}=5V

Symbol	Parameter	Min	Typ	Max	Unit
Fop	Operating frequency range	16		24	GHz
G	Small signal gain (1)	24	26		dB
ΔG	Small signal gain flatness (1)		±1		dB
Is	Reverse isolation (1)		50		dB
NF	Noise figure with V _c =1.2V		2.8	3.5	dB
Gctrl	Gain control range versus V _c	15	20		dB
P1dB	Output power at 1dB compression with V _c =1.2V		11		dBm
VSWRin	Input VSWR (1)		2.5:1	3.5:1	
VSWRout	Output VSWR (1)		2.0:1	3:1	
Vd	DC voltage V ₅ = V _{d2,3,4} V _c	-1.5	5 [-0.7, +1.2]	+1.3	V V
Id1	Bias current (2) with V _c =1.2V		35		mA
Id	Bias current total (3) with V _c =1.2V		160		mA

(1) These values are representative of on-wafer measurements that are made without bonding wires at RF ports.

(2) For optimum noise figure, the bias current Id1 should be adjusted to 35mA with V_{g1} voltage.

(3) With Id1=35mA, adjust V_{g2,3,4} voltage for a total drain current around 160mA.

Absolute Maximum RatingsT_{amb.} = 25°C (1)


Symbol	Parameter	Values	Unit
Vd	Drain bias voltage	5.5	V
Vc	Control bias voltage	1.5	V
Id	Drain bias current	250	mA
Vg	Gate bias voltage	-2.0 to +0.4	V
Pin	Maximum peak input power overdrive (2)	+15	dBm
Ta	Operating temperature range	-40 to +85	°C
Tstg	Storage temperature range	-55 to +155	°C

(1) Operation of this device above anyone of these parameters may cause permanent damage.


(2) Duration < 1s.

Typical on wafer Measurements

Bias Conditions: $V_5=V_{d2,3,4}=5V$, V_{g1} for $I_{d1}=35mA$, $V_g=-0.3V$, $V_c=+1.2V$



Gain & Noise Figure versus frequency




Typical on-wafer Gain & Return Loss


In jig Measurements

Bias Conditions: $V_5=V_{d2,3,4}=5V$, $V_{g1}=V_g=-0.3V$, $V_c=+1.2V$


All these measurements include the jig losses (about 0.5dB on gain, 0.2dB on noise figure and 0.3dB on output power).




Gain & Output power @ 18-20 GHz




Gain & Output power @ 22-24 GHz

Gain & Noise Figure versus V_c


Chip Assembly and Mechanical Data



Note : Supply feed should be capacitively bypassed. 25 μ m diameter gold wire is recommended
Bond Pad:100 x 100 μ m

**Bonding pad positions**

(Chip thickness : 100 μ m. All dimensions are in micrometers)



Ordering Information

Chip form : CHA2292-99F/00

Information furnished is believed to be accurate and reliable. However **United Monolithic Semiconductors S.A.S.** assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of **United Monolithic Semiconductors S.A.S.** Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. **United Monolithic Semiconductors S.A.S.** products are not authorised for use as critical components in life support devices or systems without express written approval from **United Monolithic Semiconductors S.A.S.**

