

1200 ~ 1600 MHz Low Noise Amplifier¹

Key Features:

Broad Frequency Range:	1145 ~ 1635 MHz
High Gain:	35.5 dB
Low Noise Figure	0.7 dB
P _{1dB} :	+3 dBm
Single DC Supply:	43 mA @ +5V
Package:	SMT, 0.50"x0.35"x0.08"
Built-in Functions:	Limiter at input port for protection, Bias-T and limiter at RF output port


Photo not available

RLAS1216M is designed to meet the rugged standards of MIL-STD-202 and MIL-STD-883.

Electrical Specifications: (at +25 °C)

Testing Item	Symbol	Test Condition	Min	Nom	Max	Unit
Frequency Range	BW		1145		1635	MHz
Gain	S ₂₁	1145 ~ 1635 MHz	34	35.5	37	dB
Gain Variation	ΔG	1145 ~ 1635 MHz		+/- 0.75	+/-1.0	dB
Input VSWR	S ₁₁	1145 ~ 1635 MHz		1.25:1	1.5:1	
Output VSWR	S ₂₂	1145 ~ 1635 MHz		1.25:1	1.5:1	
Reverse Isolation	S ₂₁	1145 ~ 1635 MHz				
Noise Figure	NF	1145 ~ 1635 MHz		0.7	0.85	dB
Output Power @ 1dB Compression	P _{1dB}	1145 ~ 1635 MHz		3	5	dBm
Output IP3	OIP3	1145 ~ 1635 MHz		TBD		dBm
Current Consumption	I _{dd}	V _{dd} = +5 V	30	43	50	mA
Power Supply Voltage	V _{dd}		+4.5	+5	+5.5	V
Thermal Resistance	R _{th,c}	Junction to case			215	°C/W
Operating Temperature	T _o		-40		+85	°C
Maximum Input Power with Limiter	P _{in,MAX}	1145 ~ 1635 MHz			+30	dBm

Outline Drawing



¹ Specifications are subject to change without notice.

Ordering Information

Part Number	RLAS1216M
--------------------	-----------

Richardson RFPD, Inc.
40W267 Keslinger Road
P.O. Box 307
LaFox, IL 60147
Telephone: (800) 737-6937
(630) 208-2700
Fax: (630) 208-2662
Internet: www.richardsonrfpd.com

IMPORTANT NOTICE

RICHARDSON RFPD, INC. AND ITS AFFILIATES RESERVE THE RIGHT TO MAKE CHANGES TO THE PRODUCT(S) OR INFORMATION CONTAINED HEREIN WITHOUT NOTICE. RICHARDSON RFPD, INC. ASSUMES NO RESPONSIBILITY FOR ANY ERRORS WHICH MAY APPEAR IN THIS DOCUMENT.

WARRANTY INFORMATION APPLICABLE TO THE PRODUCT IDENTIFIED HEREIN IS AVAILABLE UPON REQUEST. NOTHING CONTAINED HEREIN SHALL CONSTITUTE A WARRANTY, REPRESENTATION OR GUARANTEE OF ANY KIND. RICHARDSON RFPD, INC. EXPRESSLY DISCLAIMS ALL OTHER WARRANTIES, EXPRESS AND/OR IMPLIED INCLUDING BUT NOT LIMITED TO WARRANTIES OF MERCHANTABILITY, AND OF FITNESS FOR A PARTICULAR PURPOSE, USE OR APPLICATION.

NO PART OF THIS DOCUMENT MAY BE COPIED OR REPRODUCED IN ANY FORM OR BY ANY MEANS WITHOUT THE PRIOR WRITTEN CONSENT OF RICHARDSON RFPD, INC.

WARNING

RICHARDSON RFPD, INC. PRODUCTS ARE NOT INTENDED FOR USE IN LIFE SUPPORT APPLIANCES, DEVICES OR SYSTEMS. USE OF A RICHARDSON RFPD, INC. PRODUCT IN ANY SUCH APPLICATION WITHOUT WRITTEN CONSENT IS PROHIBITED.