

Делители - сумматоры мощности

Модель	Частотный диапазон,(MHz)	Вносимые потери, (dB) [Ном./Макс.]	Разбаланс амплитуды, (dB) [Ном./Макс.]	Разбаланс фазы (град.) [Ном./Макс.]	Изоляция(dB) [Ном./Мин.]	Макс. уровеньвх. Мощности, (W)
2-направления						
SPD-C1	0.01 - 100	0.4/1.0	0.1/0.2	1.0/2.0	25/20	1
DSK-701	0.01 - 100	0.5/1.0	0.1/0.2	1.0/2.0	25/20	1
SPD-C2	0.1 - 150	0.4/0.7	0.05/0.2	0.5/2.0	28/20	1
DSK-7A2B	0.25 - 300	0.4/1.0	0.15/0.3	2.0/5.0	25/20	1
DSK-7E4	1 - 750	0.8/1.0	0.15/0.3	2.0/4.0	25/20	1
DSK-719S	1 - 3000	0.6/1.0	0.1/0.4	0.5/3.0	18/13	1
SD-1	2 - 300	0.8/1.0	0.3/0.5	1.0/5.0	25/20	1
DSK-7M2B	2 - 350	0.4/0.8	0.08/0.2	0.2/2.0	32/26	1
SDL-100	2 - 1000	1.2/1.5	0.3/0.6	2.0/4.0	27/17	1
SD-2	5 - 500	0.6/1.0	0.1/0.5	0.5/5.0	25/20	1
SD2200	5 - 2000	0.8/1.5	0.2/0.7	1.5/5.0	18/15	1
DSK-726S	5 - 2000	1.5/1.9	0.05/0.4	1.8/5.0	28/15	1
DSK-709	10 - 1000	0.6/0.8	0.1/0.25	1.0/3.0	30/25	1
SD-3	10 - 1000	1.0/1.5	0.25/0.7	1.2/7.0	25/17	1
SDL-3	10 - 1000	1.0/1.5	0.25/0.7	1.2/7.0	25/17	1
SDL-6	20 - 2000	0.8/1.5	0.2/0.5	2.0/5.0	25/15	1
SPD-C12	400 - 2700	1.0/1.5	0.4/0.5	4.0/6.0	25/20	1
SDL-4	500 - 1500	1.0/1.4	0.4/0.7	4.0/7.0	20/13	1
M2D810	800 - 1000	0.5/0.8	0.2/0.5	2.0/5.0	20/14	1

DSK-729S	800 - 2200	0.5/0.8	0.05/0.4	1.0/2.0	25/20	10
SPD-95-215	950 - 2150	1.7/2.2	0.2/0.5	3.0/6.0	18/15	1
P2D100800	1000 - 8000	0.6/1.1	0.05/0.2	1.0/2.0	28/22	20
DSK100800	1000 - 8000	0.6/1.1	0.05/0.2	1.0/2.0	28/22	20
DHK-H1N	1700 - 2200	0.3/0.4	0.1/0.3	1.0/3.0	20/18	100
M2D1822	1800 - 2200	0.35/1.0	0.05/0.7	2.2/6.0	20/15	1
P2D180900L	1800 - 9000	0.4/0.8	0.05/0.2	1.0/2.0	27/23	20
DSK180900	1800 - 9000	0.4/0.8	0.05/0.2	1.0/2.0	27/23	20
M2D2025	2000 - 2550	0.40/1.0	0.03/0.7	0.3/6.0	20/15	1
M2D2428	2400 - 2800	0.5/1.0	0.1/0.5	1.5/5.0	20/15	1
3-направления						
DCK-7J2	1 - 500	0.7/1.2	0.2/0.4	1.0/3.0	27/18	1
SDL-110	2 - 200	0.5/1.0	0.2/0.4	1.0/3.0	38/23	1
SDL-135	5 - 760	1.3/1.8	0.4/0.75	3.5/7.0	23/18	1
SPD-3-7	20 - 1200	1.5/1.8	0.25/0.5	1.5/5.0	23/15	1
DCK-3-7	20 - 1200	1.5/1.8	0.25/0.5	1.5/5.0	23/15	1
SDL-115	720 - 800	1.0/1.4	0.3/0.7	2.0/5.0	18/15	1
SDL-137	850 - 950	1.0/1.4	0.3/0.7	2.0/5.0	17/13	1
SPD-C9	1700 - 2200	0.4/0.8	0.3/0.5	4.0/5.0	23/18	1
S3D1723	1700 - 2300	0.2/0.35	0.3/0.6	2.0/3.0	22/16	5
4-направления						
SDL-140	1 - 100	0.7/1.0	0.2/0.4	1.0/3.0	25/20	1

DDK-702S	1 - 250	0.7/1.2	0.1/0.3	1.0/4.0	30/20	1
DSK-7E2B	1 - 200	0.7/1.2	0.1/0.3	2.0/5.0	25/20	1
SPD-5-1000	5 - 1000	0.65/1.0	0.1/0.5	2.0/5.0	25/20	1
SD-4-1	5 - 1000	0.9/1.9	0.4/0.9	4.0/7.0	30/15	1
DDK-1000S	5 - 1000	0.85/1.2	0.1/0.5	2.0/5.0	23/20	1
SPD-5-1500	5 - 1500	1.3/2.0	0.35/0.5	3.5/5.0	25/20	1
DSK-745S	5 - 2000	2.3/2.8	0.2/0.6	2.0/5.0	20/15	1
SDL-120	20 - 400	1.3/1.8	0.6/0.75	3.0/7.0	25/17	1
DSK-H3N	800 - 2400	0.5/0.8	0.25/0.5	1.0/4.0	23/18	30
SPD-90-210	900 - 2100	0.9/1.25	0.2/0.5	3.0/6.0	20/15	1
M4D1626	1600 - 2600	0.5/1.2	0.4/0.7	3.0/7.0	22/12	1
M4D1720	1700 - 2000	0.5/0.8	0.2/0.5	2.3/7.0	22/16	1
M4D3236	3200 - 3600	0.3/1.0	0.1/0.5	2.0/6.0	20/15	1
5-направлений						
DES-901	0.5 - 30	0.7/1.0	0.1/0.3	0.25/4.0	25/20	1
DEK-701S	0.5 - 30	0.7/1.0	0.1/0.3	0.25/4.0	25/20	1
DES-902	1 - 300	1.5/2.0	0.5/0.6	2.5/8.0	25/17	1
DEK-7G2S	1 - 300	1.5/2.0	0.5/0.6	2.5/8.0	25/17	1
6-направлений						
DFS-9B1	1 - 100	0.5/0.9	0.05/0.3	0.8/2.0	30/25	1
DFK-7B1S	1 - 100	0.5/0.9	0.05/0.3	0.8/2.0	30/25	1
DFK-704B	1 - 250	0.5/1.0	0.2/0.3	2.0/3.0	28/25	1

DFS-905	1 - 500	1.0/1.8	0.2/0.6	4.0/8.0	23/15	1
DFK-705S	1 - 500	1.0/1.8	0.2/0.6	4.0/8.0	23/15	1
8-направлений						
DSS-914	0.01-30	0.6/1.1	0.1/0.3	1.0/4.0	35/23	1
DHK-714S	0.01-30	0.6/1.1	0.1/0.3	1.0/4.0	35/23	1
DSK-714B	0.01-30	0.7/1.0	0.1/0.3	1.0/4.0	35/23	1
DHK-701S	1-100	1.2/1.4	0.2/0.4	1.0/4.0	33/30	1
DHS-902	1-200	0.8/1.2	0.1/0.3	1.5/4.0	25/20	1
DHK-702S	1-200	0.8/1.2	0.1/0.3	1.5/4.0	25/20	1
DSK-773B	5-200	0.7/1.2	0.1/0.3	3.0/6.0	25/20	1
DSS-585	5-1000	1.6/2.0	0.2/0.5	2.0/5.0	30/25	1
DHK-585S	5-1000	1.6/2.0	0.2/0.5	2.0/5.0	30/25	1
DHK1100	10-1000	1.3/1.8	0.3/0.6	3.0/6.0	23/18	0.5
10-направлений						
DXP-9A2	1 - 150	1.0/1.3	0.1/0.3	3.0/6.0	23/18	1
DHK-702B	5 - 200	1.2/1.5	0.4/0.8	4.0/8.0	25/20	1
DSK-714B	5 - 200	1.2/1.6	0.4/0.8	4.0/8.0	25/18	1
12-направлений						
DLP-901	2 - 100	0.6/1.0	0.2/0.6	2.0/3.0	34/20	1
DLK-712S	3 - 250	1.6/2.0	0.4/0.8	4.0/8.0	30/23	1
DLK-702B	5 - 200	1.2/1.5	0.4/0.8	4.0/8.0	25/20	1
DLK-772B	5 - 200	1.2/1.6	0.4/0.8	4.0/8.0	25/18	1

DLK-7L4S	850 - 1000	3.0/4.0	1.0/2.0	4.0/8.0	20/15	1
16-направлений						
DPK1100	10 - 1000	2.0/2.5	0.7/1.2	6.0/12	20/15	0.5



The Signal Source Noise Control & Signal Processing Experts.