

Направленные ответвители						
Модель	Диапазон частот,(MHz)	Ответвление, (dB) [Ном.]	Неравномерность ответвления, (dB)	Прямые потери, (dB) [Ном./Макс.]	Направленность, (dB) [Ном./Мин.]	Макс. уровень вх. мощности, (W)
KBK-703	1 - 500	11.25 ±0.5	±0.6	0.6/1.0	32/20	1
KBK-7C4	1 - 1000	11.0 ±0.5	±0.5	1.2/2.0	26/20	1
SDC5100D	5 - 1000	20 ±0.5	±0.5	0.45/0.95	30/18	1
SC-4B	5 - 1000	10.7 ±0.5	±0.5	0.8/1.6	35/15	1
KBK-708S	10 - 2000	9.8 ±0.8	±1.0	2.4/3.0	22/13	1
SDC-C7	10 - 2000	9.8 ±0.8	±1.0	2.4/3.0	17/13	1
KBS-10-225	225 - 400	10.5 ±1.0	±0.5	0.6/0.7	25/18	50
KDS-20-225	225 - 400	20 ±1.0	±0.5	0.2/0.4	25/18	50
KBK-10-225	225 - 400	10.5 ±1.0	±0.5	0.6/0.7	25/18	50
KDK-20-225	225 - 400	20.0 ±1.0	±0.5	0.2/0.4	25/18	50
SCS100800-10	1000 - 8000	10.5 ±1.5	±1.75	1.2/1.5	18/7	25
KBK100800-10	1000 - 8000	10.5 ±1.5	±1.75	1.2/1.5	18/7	25
SCS100800-20	1000 - 8000	20.5 ±1.5	±2.5	0.45/0.75	14/5	25
KDK100800-20	1000 - 8000	20.5 ±1.5	±2.5	0.45/0.75	18/5	25
KEK-704DH-2	850 - 1250	30.0 ±1.5	±0.25	0.0/0.3	/25	500