

**DATA SHEET**


# SMV1493, SMV1494: Silicon Abrupt Junction Tuning Varactors, Packaged and Bondable Mesa Chips

## Applications

- RF and UHF VCOs
- Voltage tuned filters
- Voltage variable phase shifters

## Features

- Supports high frequencies to beyond 56 GHz
- Low series resistance for low phase noise
- Packages rated MSL1, 260 °C per JEDEC J-STD-020

 Skyworks Pb-free products are compliant with all applicable legislation. For additional information, refer to *Skyworks Definition of Lead (Pb)-Free*, document number SQ04-0073.







## Description

The SMV1493 and SMV1494 bare die and hermetic packaged silicon abrupt junction varactor diodes are designed for use in Voltage Controlled Oscillators (VCOs) requiring tight capacitance tolerances. The low resistance of these varactors makes them appropriate for high-Q resonators in wireless system VCOs from RF to frequencies beyond 56 GHz.

Table 1 lists the various packages and part numbers for the SMV1493 and SMV1494 varactors.

**Table 1. Hermetic Packaged Abrupt Junction Tuning Varactor Chips**

			
<b>Hermetic Stripline 240</b>	<b>Hermetic Pill 203</b>	<b>Stripline 219</b>	<b>Coaxial 210</b>
SMV1493-240	SMV1493-203	SMV1493-219	SMV1493-210
SMV1494-240	SMV1494-203	SMV1494-219	SMV1494-210
Ls = 0.55 nH	Ls = 0.40 nH	Ls = 0.50 nH	Ls = 0.45 nH

**Table 2. SMV1493 and SMV1494 Absolute Maximum Ratings**

Parameter	Symbol	Minimum	Maximum	Units
Forward current	I <sub>F</sub>		20	mA
Power dissipation	P <sub>D</sub>		250	mW
Operating temperature	T <sub>OP</sub>	-55	+125	°C
Storage temperature	T <sub>STG</sub>	-55	+150	°C

**Note:** Exposure to maximum rating conditions for extended periods may reduce device reliability. There is no damage to device with only one parameter set at the limit and all other parameters set at or below their nominal value. Exceeding any of the limits listed here may result in permanent damage to the device.

**CAUTION:** Although these devices are designed to be as robust as possible, Electrostatic Discharge (ESD) can damage them. These devices must be protected at all times from ESD. Static charges may easily produce potentials of several kilovolts on the human body or equipment, which can discharge without detection. Industry-standard ESD precautions should be used at all times. The SMV1493 and SMV1494 varactors are Class 0 Human Body Model (HBM) ESD devices.

**Table 3. SMV1493 and SMV1494 Electrical Specifications (Note 1)**  
(T<sub>OP</sub> = 25 °C, Unless Otherwise Noted)

Part Number	Min. V <sub>B</sub> , I <sub>R</sub> @ 10 μA (V)	C <sub>J</sub> @ 1 V (pF)	C <sub>J</sub> @ 4 V (pF)	Max. R <sub>s</sub> @ 1 V, 500 MHz (Ω)	Outline Drawing
SMV1493	12	17.4 to 20.0	9.87 to 11.97	0.50	150-802
SMV1494	12	36.3 to 41.7	20.57 to 25.07	0.45	150-802

**Note 1:** Performance is guaranteed only under the conditions listed in this Table.

### Electrical and Mechanical Specifications

The absolute maximum ratings of the SMV1493 and SMV1494 varactors are provided in Table 2. Electrical specifications are provided in Table 3. Typical capacitance values are listed in Table 4. The typical capacitance versus reverse voltage performance of the SMV1493 and SMV1494 varactors is illustrated in Figure 1.

The SPICE model for the SMV1493 and SMV1494 varactors is shown in Figure 2 and the associated model parameters are provided in Table 5.

Package dimensions are shown in Figures 3 to 7. The SMV1493 and SMV1494 varactors are not delivered on carrier tapes.

### Package and Handling Information

Instructions on the shipping container label regarding exposure to moisture after the container seal is broken must be followed. Otherwise, problems related to moisture absorption may occur when the part is subjected to high temperature during solder assembly.

The SMV1493 and SMV1494 varactors are rated to Moisture Sensitivity Level 1 (MSL1) at 260 °C. They can be used for lead or lead-free soldering. For additional information, refer to the Skyworks Application Note, *Solder Reflow Information*, document number 200164.

Care must be taken when attaching this product, whether it is done manually or in a production solder reflow environment.

**Table 4. Capacitance vs Reverse Voltage**

V <sub>R</sub> (V)	C <sub>T</sub> (pF)	
	SMV1493	SMV1494
0	28.7	57.8
0.2	25.6	51.5
0.4	23.3	46.9
0.6	21.5	43.4
0.8	20.1	40.5
1.0	19.0	38.4
1.2	17.9	36.3
1.4	17.0	34.6
1.6	16.2	33.0
1.8	15.5	31.6
2.0	15.0	30.6
2.2	14.4	29.5
2.4	13.9	28.5
2.6	13.5	27.6
2.8	13.1	26.7
3.0	12.7	26.1
3.2	12.4	25.3
3.4	12.0	24.7
3.6	11.7	24.1
3.8	11.4	23.5
4.0	11.2	23.1
4.2	10.9	22.6
4.4	10.7	22.1
4.6	10.5	21.7
4.8	10.3	21.3
5.0	10.1	20.9
6.0	9.2	19.2
7.0	8.5	17.9
8.0	8.0	16.7
9.0	7.6	15.7
10.0	7.1	14.7

### Typical Performance Characteristics




Figure 1. Capacitance vs Reverse Voltage




Figure 2. SPICE Model


Table 5. SPICE Model Parameters

Part Number	C <sub>J0</sub> (pF)	V <sub>J</sub> (V)	M	C <sub>P</sub> (pF)	R <sub>S</sub> (Ω)
SMV1493	28.66	0.88	0.55	0	0.50
SMV1494	57.70	0.83	0.52	0	0.45

Values extracted from measured performance.

For package inductance, L<sub>s</sub>, refer to Table 1.


For more details, refer to the Skyworks Application Note, *Varactor SPICE Model for Approved RF VCO Applications*, document number 200315.



Dimensions are in inches (millimeters shown in parentheses)

S1566a


Figure 3. 150-802 Die Dimensions




Dimensions are in inches (millimeters shown in parentheses)

S1569


Figure 4. -203 Package Dimensions



**Figure 5. -210 Package Dimensions**



**Figure 6. -219 Package Dimensions**



**Figure 7. -240 Package Dimensions**

**DATA SHEET • SMV1493 AND SMV1494 VARACTORS**

Copyright © 2008, 2011 Skyworks Solutions, Inc. All Rights Reserved.

Information in this document is provided in connection with Skyworks Solutions, Inc. ("Skyworks") products or services. These materials, including the information contained herein, are provided by Skyworks as a service to its customers and may be used for informational purposes only by the customer. Skyworks assumes no responsibility for errors or omissions in these materials or the information contained herein. Skyworks may change its documentation, products, services, specifications or product descriptions at any time, without notice. Skyworks makes no commitment to update the materials or information and shall have no responsibility whatsoever for conflicts, incompatibilities, or other difficulties arising from any future changes.

No license, whether express, implied, by estoppel or otherwise, is granted to any intellectual property rights by this document. Skyworks assumes no liability for any materials, products or information provided hereunder, including the sale, distribution, reproduction or use of Skyworks products, information or materials, except as may be provided in Skyworks Terms and Conditions of Sale.

THE MATERIALS, PRODUCTS AND INFORMATION ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, WHETHER EXPRESS, IMPLIED, STATUTORY, OR OTHERWISE, INCLUDING FITNESS FOR A PARTICULAR PURPOSE OR USE, MERCHANTABILITY, PERFORMANCE, QUALITY OR NON-INFRINGEMENT OF ANY INTELLECTUAL PROPERTY RIGHT; ALL SUCH WARRANTIES ARE HEREBY EXPRESSLY DISCLAIMED. SKYWORKS DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. SKYWORKS SHALL NOT BE LIABLE FOR ANY DAMAGES, INCLUDING BUT NOT LIMITED TO ANY SPECIAL, INDIRECT, INCIDENTAL, STATUTORY, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS THAT MAY RESULT FROM THE USE OF THE MATERIALS OR INFORMATION, WHETHER OR NOT THE RECIPIENT OF MATERIALS HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Skyworks products are not intended for use in medical, lifesaving or life-sustaining applications, or other equipment in which the failure of the Skyworks products could lead to personal injury, death, physical or environmental damage. Skyworks customers using or selling Skyworks products for use in such applications do so at their own risk and agree to fully indemnify Skyworks for any damages resulting from such improper use or sale.

Customers are responsible for their products and applications using Skyworks products, which may deviate from published specifications as a result of design defects, errors, or operation of products outside of published parameters or design specifications. Customers should include design and operating safeguards to minimize these and other risks. Skyworks assumes no liability for applications assistance, customer product design, or damage to any equipment resulting from the use of Skyworks products outside of stated published specifications or parameters.

Skyworks, the Skyworks symbol, and "Breakthrough Simplicity" are trademarks or registered trademarks of Skyworks Solutions, Inc., in the United States and other countries. Third-party brands and names are for identification purposes only, and are the property of their respective owners. Additional information, including relevant terms and conditions, posted at [www.skyworksinc.com](http://www.skyworksinc.com), are incorporated by reference.