


Single switch with Series diode MOSFET Power Module

$$V_{DSS} = 1000V$$

$$R_{DSon} = 45m\Omega \text{ typ @ } T_j = 25^\circ C$$

$$I_D = 215A \text{ @ } T_c = 25^\circ C$$



Application


- Zero Current Switching resonant mode

Features

- Power MOS 7[®] MOSFETs
 - Low R_{DSon}
 - Low input and Miller capacitance
 - Low gate charge
 - Avalanche energy rated
 - Very rugged
- Kelvin source for easy drive
- Very low stray inductance
 - Symmetrical design
 - M5 power connectors
- High level of integration
- AlN substrate for improved thermal performance

Benefits

- Outstanding performance at high frequency operation
- Direct mounting to heatsink (isolated package)
- Low junction to case thermal resistance
- Low profile
- RoHS Compliant



Absolute maximum ratings

Symbol	Parameter	Max ratings	Unit
V_{DSS}	Drain - Source Breakdown Voltage	1000	V
I_D	Continuous Drain Current	$T_c = 25^\circ C$ 215	A
		$T_c = 80^\circ C$ 160	
I_{DM}	Pulsed Drain current	860	
V_{GS}	Gate - Source Voltage	± 30	V
R_{DSon}	Drain - Source ON Resistance	52	$m\Omega$
P_D	Maximum Power Dissipation	$T_c = 25^\circ C$ 5000	W
I_{AR}	Avalanche current (repetitive and non repetitive)	30	A
E_{AR}	Repetitive Avalanche Energy	50	mJ
E_{AS}	Single Pulse Avalanche Energy	3200	

CAUTION: These Devices are sensitive to Electrostatic Discharge. Proper Handling Procedures Should Be Followed. See application note APT0502 on www.microsemi.com

All ratings @ $T_j = 25^\circ\text{C}$ unless otherwise specified

Electrical Characteristics

Symbol	Characteristic	Test Conditions	Min	Typ	Max	Unit
I_{DSS}	Zero Gate Voltage Drain Current	$V_{GS} = 0V, V_{DS} = 1000V$ $T_j = 25^\circ\text{C}$			600	μA
		$V_{GS} = 0V, V_{DS} = 800V$ $T_j = 125^\circ\text{C}$			3	mA
$R_{DS(on)}$	Drain – Source on Resistance	$V_{GS} = 10V, I_D = 107.5A$		45	52	$\text{m}\Omega$
$V_{GS(th)}$	Gate Threshold Voltage	$V_{GS} = V_{DS}, I_D = 30\text{mA}$	3		5	V
I_{GSS}	Gate – Source Leakage Current	$V_{GS} = \pm 30V, V_{DS} = 0V$			± 600	nA

Dynamic Characteristics

Symbol	Characteristic	Test Conditions	Min	Typ	Max	Unit
C_{iss}	Input Capacitance	$V_{GS} = 0V$		42.7		nF
C_{oss}	Output Capacitance	$V_{DS} = 25V$		7.6		
C_{rss}	Reverse Transfer Capacitance	$f = 1\text{MHz}$		1.3		
Q_g	Total gate Charge	$V_{GS} = 10V$		1602		nC
Q_{gs}	Gate – Source Charge	$V_{Bus} = 500V$		204		
Q_{gd}	Gate – Drain Charge	$I_D = 215A$		1038		
$T_{d(on)}$	Turn-on Delay Time	Inductive switching @ 125°C $V_{GS} = 15V$ $V_{Bus} = 670V$ $I_D = 215A$ $R_G = 0.5\Omega$		18		ns
T_r	Rise Time			14		
$T_{d(off)}$	Turn-off Delay Time			140		
T_f	Fall Time			55		
E_{on}	Turn-on Switching Energy	Inductive switching @ 25°C $V_{GS} = 15V, V_{Bus} = 670V$ $I_D = 215A, R_G = 0.5\Omega$		7.2		mJ
E_{off}	Turn-off Switching Energy			4.3		
E_{on}	Turn-on Switching Energy	Inductive switching @ 125°C $V_{GS} = 15V, V_{Bus} = 670V$ $I_D = 215A, R_G = 0.5\Omega$		12		mJ
E_{off}	Turn-off Switching Energy			5.8		

Series diode ratings and characteristics


Symbol	Characteristic	Test Conditions		Min	Typ	Max	Unit	
V _{RRM}	Maximum Repetitive Reverse Voltage			1200			V	
I _{RM}	Maximum Reverse Leakage Current	V _R =1200V	T _j = 25°C			600	μA	
			T _j = 125°C			2000		
I _F	DC Forward Current		T _j = 80°C		360		A	
V _F	Diode Forward Voltage	I _F = 360A			2.5	3	V	
		I _F = 720A			3			
		I _F = 360A	T _j = 125°C		1.8			
t _{rr}	Reverse Recovery Time	I _F = 360A V _R = 800V di/dt = 1200A/μs	T _j = 25°C		265		ns	
			T _j = 125°C		350			
Q _{rr}	Reverse Recovery Charge			T _j = 25°C		3.3		μC
				T _j = 125°C		17.3		

Thermal and package characteristics

Symbol Characteristic






			Min	Typ	Max	Unit
R_{thJC}	Junction to Case Thermal Resistance	Transistor			0.025	°C/W
		Series diode			0.16	
V_{ISOL}	RMS Isolation Voltage, any terminal to case $t=1$ min, $I_{isol}<1mA$, 50/60Hz		2500			V
T_J	Operating junction temperature range		-40		150	°C
T_{STG}	Storage Temperature Range		-40		125	
T_C	Operating Case Temperature		-40		100	
Torque	Mounting torque	To Heatsink	M6	3	5	N.m
		For teminals	M5	2	3.5	
Wt	Package Weight				280	g







SP6 Package outline (dimensions in mm)









See application note APT0601 - Mounting Instructions for SP6 Power Modules on www.microsemi.com

Typical Performance Curve







Microsemi reserves the right to change, without notice, the specifications and information contained herein

Microsemi's products are covered by one or more of U.S. patents 4,895,810 5,045,903 5,089,434 5,182,234 5,019,522 5,262,336 6,503,786 5,256,583 4,748,103 5,283,202 5,231,474 5,434,095 5,528,058 and foreign patents. U.S. and Foreign patents pending. All Rights Reserved.