# MACS-007802-0M1R10



## Stereo Doppler Transceiver 24.125 GHz

M/A-COM Products Rev. -

#### **Features**

- Low Cost
- 10mW Output Power
- Gold Plated Solder Pins
- **Detects Direction of Motion**
- Rugged Die cast Construction
- 10Hz 5000Hz IF Bandwidth
- Lead Free (RoHS\* Compliant)

### **Description and Applications**

M/A-COM's MACS-007802-0M1R10 is a RoHS Compliant K-Band Stereo Doppler transceiver consisting of a Gunn Diode oscillator and two Schottky Diode mixers assembled into a die cast waveguide package.

These Transceivers are well suited for high volume applications where small size and reliability are required. Typical applications include automatic door openers, police radar and presence sensing applications, where Direction of motion is required.

## **Product Specifications**

Parameter	Test Conditions	Units	Min.	Тур.	Max.	
Operating Frequency	+25 °C	GHz	24.100	24.125	24.150	
Output Power	+25 °C	mW	10.0			
Operating Current	+25 °C	mA	140	175	200	
Operating Voltage	+25 °C	VDC		5.0		
Schottky Diode Noise	+25 °C	micro- Volts		2.5	5.0	
Transceiver Sensitivity	+25 °C	-dBc	-90	-103		
Mixer Phasing	+25 °C	Degrees	50		120	

Operating temperature to full specification -30°C to +70°C

# Absolute Maximum Ratings<sup>1</sup>

Parameter	Maximum Ratings		
Operating Temperature	-40 °C to +85 °C		
Storage Temperature	-65 °C to +150 °C		
Incident RF Input Power	+20 dBm		
DC Input (Gunn Diode)	+5.5VDC		
Soldering Temperature	+260 °C max.		

1. Exceeding these limits may cause permanent damage.

Note: Device is ESD Sensitive. Proper ESD Precautions should be used when handling this Device..


### **Package Outline**



### **PIN Configuration**

PIN	Function	
1	DC Input	
2	GND	
3	IF Output (Mixer 1)	
4	IF Output (Mixer 2)	

## **Functional Block Diagram**





\*Restrictions on Hazardous Substances, European Union Directive 2002/95/EC.

ADVANCED: Data Sheets contain information regarding a product MA-COM Technical Solutions is considering for development. Performance is based on target specifications, simulated results, and/ or prototype measurements. Commitment to develop is not guaranteed.

PRELIMINARY: Data Sheets contain information regarding a product MA-COM Technical Solutions has under development. Performance is based on engineering tests. Specifications are typical. Mechanical outline has been fixed. Engineering samples and/or test data may be available. Commitment to produce in volume is not guaranteed.

- North America Tel: 800.366.2266 / Fax: 978.366.2266
- Europe Tel: 44.1908.574.200 / Fax: 44.1908.574.300
- Asia/Pacific Tel: 81.44.844.8296 / Fax: 81.44.844.8298 Visit www.macom.com for additional data sheets and product information.


MA-COM Technical Solutions and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice.


# MACS-007802-0M1R10




Stereo Doppler Transceiver 24.125 GHz

M/A-COM Products Rev. -







- Europe Tel: 44.1908.574.200 / Fax: 44.1908.574.300
- Asia/Pacific Tel: 81.44.844.8296 / Fax: 81.44.844.8298 Visit www.macom.com for additional data sheets and product information.