

Синтезаторы на несколько фиксированных частот

Модель	Рабочий диапазон частот, MHz	Частота внешнего опорного генератора (MHz)	Минимальный уровень вых. мощности, dBm	Уровень фазовых шумов на отстройке, dBc/Hz	
				@10 kHz	@100 kHz
FCPL511-10	50 - 110	10	+6	-116	-125
FCPL-70	65 - 72	10	-1	-112	-131
FCPL610-10	65 - 102.5	10	-3	-110	-125
FCPL1114-5	112.5 - 140	10	+7	-115	-132
FCPL3239-10	320 - 390	10	-1	-108	-120
FCPL3644-26	360 - 440	26	+4	-100	-120
FCPL5460-10	540 - 605	10	+5	-108	-116
FCPL65120-10	650 - 1200	10	+7	-102	-116
FCPL840-10	840 - 840	10	+3	-101	-120
FCPH90110-15	900 - 1100	15	+7	-93	-113
FCPH100120-15	1000 - 1200	15	+7	-93	-113
FCPH100125-10	1000 - 1250	10	+5	-100	-112
LFCPH100145-10	1000 - 1450	10	+7	-98	-114
FCPH110175-10	1100 - 1750	10	+7	-102	-113
LFCPH181254-10	1800 - 2540	10	+5	-90	-110

FCPH183187-10	1830 - 1870	10	-2	-98	-112
FCPH243250-100	2430 - 2505	100	-1	-97	-116
FCPH243290-10	2430 - 2900	10	+7	-90	-110
FCPH310410-10	3100 - 4100	10	+5	-92	-96



The Signal Source Noise Control & Signal Processing Experts.